SAFETY DATA SHEET



1/13

according to 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Easy-Mix PU-240 Polyurethane Adhesive Resin

Section 1. Identification

| GHS product identifier | : | Easy-Mix PU-240 Polyurethane Adhesive Resin |
|------------------------|---|---|
| Product code | : | 107531 |

Relevant identified uses of the substance or mixture and uses advised against

Not available.

| Supplier's details | : WEICON Canada Inc. 20 Steckle Place, Unit 20 Kitchener, Ontario N2E 2C3, CA www.weicon.ca E-mail: info@weicon.ca Telephone: +1-519-896-5252 Telefax: +1-519-896-5254 |
|--|--|
| e-mail address of person responsible for this SDS | : msds@weicon.de |
| Emergency telephone number | : +1 202 464 2554 / TRANSPORT EMERGENCY CONTACT - USA (24h): Tel: +1 202 464 2554 |

Section 2. Hazards identification

| OSHA/HCS status | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). |
|--|---|
| Classification of the substance or mixture | : ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 |
| <u>GHS label elements</u> Hazard pictograms | |
| Signal word | : Danger |
| Hazard statements | : H315 - Causes skin irritation. |

| | H317 - May cause an allergic skin reaction. |
|--------------------------|--|
| | H319 - Causes serious eye irritation. |
| | H332 - Harmful if inhaled. |
| | H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| | H335 - May cause respiratory irritation. |
| | H351 - Suspected of causing cancer. |
| | H373 - May cause damage to organs through prolonged or repeated exposure. |
| Precautionary statements | |
| Prevention | P280 - Wear protective gloves, protective clothing and eye or face protection. P271 - Use only outdoors or in a well-ventilated area. P260 - Do not breathe vapor. |
| | |

Section 2. Hazards identification

| Response | : P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
|-------------------------------------|---|
| | P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor. |
| Storage | : Not applicable. |
| Disposal | : P501 - Dispose of waste according to applicable legislation. |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

| % | CAS number |
|-----------|------------------------|
| ≥10 - ≤25 | 9016-87-9 |
| ≥10 - ≤25 | 25686-28-6 |
| ≤10 | 101-68-8 |
| | ≥10 - ≤25 ≥10 - ≤25 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Section 4. First aid measures

Description of necessary first aid measures

| Eye contact | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
|--------------|---|
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or symptoms, avoid further exposure. |
| Skin contact | : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |

Most important symptoms/effects, acute and delayed

| Eye contact | : Causes serious eye irritation. |
|--------------|--|
| Inhalation | : Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Skin contact | : Causes skin irritation. May cause an allergic skin reaction. |
| Ingestion | : No known significant effects or critical hazards. |

| Date of issue/Date of revision : 10/20/2022 Date of previous issue | : 10/19/2022 | Version : 1.03 | 2/13 |
|--|--------------|----------------|------|
|--|--------------|----------------|------|

Section 4. First aid measures

Over-exposure signs/symptoms

| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |
|-------------------------|--|
| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing wheezing and breathing difficulties asthma |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |
| Indication of immediate | medical attention and special treatment needed, if necessary |
| Notes to physician | : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| Extinguishing media | |
|--|---|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |
| Specific hazards arising from the chemical | : In a fire or if heated, a pressure increase will occur and the container may burst. |
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides Hydrogen cyanide (HCN). |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

| Date of issue/Date of revision | : 10/20/2022 | Date of previous issue | : 10/19/2022 | Version : 1.03 |
|--------------------------------|--------------|------------------------|--------------|----------------|
| | | | | |

3/13

Section 6. Accidental release measures

| For emergency responders | : | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
|--|---|---|
| Environmental precautions | : | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
| Methods and materials for containment and cleaning up | : | Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Small spill | : | Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |

Section 7. Handling and storage

Precautions for safe handling

| Protective measures | Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. We appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. | r |
|--|---|---|
| Advice on general occupational hygiene | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. | 3 |
| Conditions for safe storage, including any incompatibilities | Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 fo incompatible materials before handling or use. | |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|--|---|
| Isocyanic acid, polymethylenepolyphenylene ester | None. |
| Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer | None. |
| 4,4'-methylenediphenyl diisocyanate | ACGIH TLV (United States, 1/2021). TWA: 0.005 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). CEIL: 0.02 ppm CEIL: 0.2 mg/m ³ NIOSH REL (United States, 10/2020). |
| Date of issue/Date of revision : 10/20/2022 Date of previous issue | e :10/19/2022 Version :1.03 4/13 |

Section 8. Exposure controls/personal protection

| | TWA: 0.05 mg/m ³ 10 hours. TWA: 0.005 ppm 10 hours. | | | |
|---|--|--|--|--|
| | CEIL: 0.2 mg/m ³ 10 minutes. CEIL: 0.02 ppm 10 minutes. | | | |
| | OSHA PEL (United States, 5/2018). | | | |
| | CEIL: 0.02 ppm | | | |
| | CEIL: 0.2 mg/m ³ | | | |
| Appropriate engineering | : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or | | | |
| controls | other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. | | | |
| Environmental exposure controls | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. | | | |
| Individual protection measur | es | | | |
| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before | | | |
| | eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. | | | |
| Eye/face protection | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. | | | |
| Skin protection | | | | |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : ; Viton®, Butyl rubber gloves. | | | |
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. | | | |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. | | | |
| Respiratory protection | : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : inorganic gases/vapors filter (Type B) | | | |
| Section 9. Physica | I and chemical properties | | | |
| Appearance | | | | |
| Physical state | : Liquid. | | | |
| Color | : Black. | | | |
| Odor | : Bland. [Strong] | | | |
| Odor threshold | : Not available. | | | |
| рН | : Not applicable. | | | |
| Melting point/freezing point | : Not available. | | | |
| Boiling point, initial boiling point, and boiling range | : Not available. | | | |

: Closed cup: >93.3°C (>199.9°F)

Flash point

| Date of issue/Date of revision | : 10/20/2022 | Date of previous issue | :10/19/2022 | Version : 1.03 | 5/13 |
|--------------------------------|--------------|------------------------|-------------|----------------|------|

Section 9. Physical and chemical properties

÷

| Evaporation rate | : | Not available. |
|---|---|---|
| Flammability | : | Highly flammable in the presence of the following materials or conditions: acids, alkalis and moisture. |
| Lower and upper explosion limit/flammability limit | : | Not available. |

Vapor pressure

| | | Vapor Pres | sure at 20°C | ۱ N | /apor pres | sure at 50°C |
|--|--------------|---------------------------------|--------------|-------|------------|--------------|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method |
| 4,4'-methylenediphenyl diisocyanate | 0 | 0 | | | | |
| Relative vapor density | : Not availa | ble. | | | | |
| Relative density | : Not availa | ble. | | | | |
| Density | : 1.28 g/cm | ³ [20°C (68° | 'F)] | | | |
| olubility(ies) | : | | | | | |
| Not available. | | | | | | |
| olubility in water | : Not availa | ble. | | | | |
| liscible with water | : No. | No. | | | | |
| artition coefficient: n- ctanol/water | : Not applic | Not applicable. | | | | |
| uto-ignition temperature | : Not applic | Not applicable. | | | | |
| Decomposition temperature | : Not availa | Not available. | | | | |
| /iscosity | : Dynamic: | Dynamic: 60000 mPa⋅s (60000 cP) | | | | |
| low time (ISO 2431) | : Not availa | Not available. | | | | |
| Particle characteristics | | | | | | |
| Median particle size | : Not applic | able. | | | | |

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|--|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : No specific data. |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects Acute toxicity

6/13

Section 11. Toxicological information

| | | 1 | | |
|---|---------------------------------|---------|-------------|----------|
| Product/ingredient name | Result | Species | Dose | Exposure |
| Isocyanic acid, polymethylenepolyphenylene ester | LC50 Inhalation Dusts and mists | Rat | 0.31 mg/l | 4 hours |
| | LC50 Inhalation Vapor | Rat | 490 mg/m³ | 4 hours |
| | LD50 Dermal | Rabbit | >9400 mg/kg | - |
| | LD50 Oral | Rat | 49 g/kg | - |
| Benzene, 1,1'-methylenebis [4-isocyanato-, homopolymer | LC50 Inhalation Dusts and mists | Rat | 0.49 mg/l | 4 hours |
| 4,4'-methylenediphenyl diisocyanate | LC50 Inhalation Dusts and mists | Rat | 0.368 mg/l | 4 hours |
| | LD50 Oral | Rat | 9200 mg/kg | - |

Acute toxicity estimates

| Route | ATE value |
|------------------------------|-----------|
| Inhalation (vapors) | 55 mg/l |
| Inhalation (dusts and mists) | 3.55 mg/l |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|--------------------------|---------|-------|----------|-------------|
| Isocyanic acid, polymethylenepolyphenylene ester | Eyes - Mild irritant | Rabbit | - | 100 mg | - |
| 4,4'-methylenediphenyl diisocyanate | Eyes - Moderate irritant | Rabbit | - | 100 mg | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|--|------|------|-----|
| Isocyanic acid, polymethylenepolyphenylene ester | - | 3 | - |
| 4,4'-methylenediphenyl diisocyanate | - | 3 | - |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Section 11. Toxicological information

| Name | Category | Route of exposure | Target organs |
|---|------------|-------------------|---------------------------------|
| Isocyanic acid, polymethylenepolyphenylene ester | Category 3 | - | Respiratory tract irritation |
| Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer | Category 3 | - | Respiratory tract irritation |
| 4,4'-methylenediphenyl diisocyanate | Category 3 | - | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|---|------------|-------------------|---------------|
| Isocyanic acid, polymethylenepolyphenylene ester | Category 2 | - | - |
| Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer | Category 2 | - | - |
| 4,4'-methylenediphenyl diisocyanate | Category 2 | - | - |

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

| Potential | acute | health | effects |
|-----------|-------|--------|---------|

| Eye contact | : Causes serious eye irritation. |
|--------------|--|
| Inhalation | Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Skin contact | : Causes skin irritation. May cause an allergic skin reaction. |
| Ingestion | : No known significant effects or critical hazards. |

Symptoms related to the physical, chemical and toxicological characteristics

| Eye contact | Adverse symptoms may include the following: pain or irritation watering redness |
|--------------|--|
| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing wheezing and breathing difficulties asthma |
| Skin contact | Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |

Delayed and immediate effects and also chronic effects from short and long term exposure

| <u>Short term exposure</u> | | |
|-------------------------------|------------------|--|
| Potential immediate | : Not available. | |
| effects | | |
| Potential delayed effects | : Not available. | |
| Long term exposure | | |
| Potential immediate | : Not available. | |
| effects | | |
| Potential delayed effects | : Not available. | |
| Potential chronic health effe | <u>ects</u> | |

| Date of issue/Date of revision | : 10/20/2022 | Date of previous issue | :10/19/2022 |
|---------------------------------|--------------|------------------------|--------------|
| Bute of 1990e, Bute of Tevision | . 10/20/2022 | Bute of previous issue | . 10/10/2022 |

Section 11. Toxicological information

Not available.

| General | : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
|-----------------------|--|
| Carcinogenicity | Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| Fertility effects | : No known significant effects or critical hazards. |

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|---|--------|-----|-----------|
| Benzene, 1,1'-methylenebis [4-isocyanato-, homopolymer | 8.56 | 200 | Low |
| 4,4'-methylenediphenyl diisocyanate | 4.51 | 200 | Low |

Mobility in soil

Soil/water partition : Not available. coefficient (K_{oc})

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IMDG | ΙΑΤΑ |
|-------------------------------|-----------------------|-----------------------|--------------------------|----------------|----------------|
| UN number | Not available. | Not available. | Not available. | Not available. | Not available. |
| UN proper shipping name | Not available. | Not available. | Not available. | Not available. | Not available. |
| Transport hazard class(es) | Not available. | Not available. | Not available. | Not available. | Not available. |
| Packing group | - | - | - | - | - |
| Environmental hazards | No. | No. | No. | No. | No. |

Special precautions for user : **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

| Ŭ | - |
|---|--|
| U.S. Federal regulations | : TSCA 8(a) PAIR: 4,4'-methylenediphenyl diisocyanate |
| | TSCA 8(a) CDR Exempt/Partial exemption: Not determined |
| | TSCA 8(c) calls for record of SAR : Isocyanic acid, polymethylenepolyphenylene ester; 4,4'-methylenediphenyl diisocyanate |
| | Clean Water Act (CWA) 307: 4,4'-methylenediphenyl diisocyanate |
| Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) | : Listed |
| Clean Air Act Section 602 Class I Substances | : Not listed |
| Clean Air Act Section 602 Class II Substances | : Not listed |
| DEA List I Chemicals (Precursor Chemicals) | : Not listed |
| DEA List II Chemicals (Essential Chemicals) | : Not listed |
| <u>SARA 302/304</u> | |
| Composition/information | on ingredients |
| No products were found. | |
| SARA 304 RQ | : Not applicable. |
| <u>SARA 311/312</u> | |
| | |
| | |

Section 15. Regulatory information

| Classification | : ACUTE TOXICITY (inhalation) - Category 4 |
|----------------|---|
| | SKIN IRRITATION - Category 2 |
| | EYE IRRITATION - Category 2A |
| | RESPIRATORY SENSITIZATION - Category 1 |
| | SKIN SENSITIZATION - Category 1 |
| | CARCINOGENICITY - Category 2 |
| | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract |
| | irritation) - Category 3 |
| | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 |
| | |

Composition/information on ingredients

| Name | % | Classification |
|---|-----------|--|
| Isocyanic acid, polymethylenepolyphenylene ester | ≥10 - ≤25 | ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 |
| Benzene, 1,1'-methylenebis [4-isocyanato-, homopolymer | ≥10 - ≤25 | ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 |
| 4,4'-methylenediphenyl diisocyanate | ≤10 | ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 |

<u>SARA 313</u>

| | Product name | CAS number | % |
|-----------------------|--|------------|-----------|
| Form R - Reporting | Isocyanic acid, polymethylenepolyphenylene ester | 9016-87-9 | ≥10 - ≤25 |
| requirements | 4,4'-methylenediphenyl diisocyanate | 101-68-8 | ≤10 |
| Supplier notification | Isocyanic acid, polymethylenepolyphenylene ester | 9016-87-9 | ≥10 - ≤25 |
| | 4,4'-methylenediphenyl diisocyanate | 101-68-8 | ≤10 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

| Massachusetts | following components are listed: METHYLENE BISPHENY | L ISOCYANATE |
|---------------|--|--------------|
| New York | following components are listed: Methylene diphenyl diisocy | yanate |
| New Jersey | following components are listed: METHYLENE DIPHENYL LYMERIC); METHYLENE BISPHENYL ISOCYANATE | DIISOCYANATE |

| Date of issue/Date of revision | : 10/20/2022 | Date of previous issue | :10/19/2022 | Version : 1.03 |
|--------------------------------|--------------|------------------------|-------------|----------------|
|--------------------------------|--------------|------------------------|-------------|----------------|

Section 15. Regulatory information

```
Pennsylvania
```

: The following components are listed: BENZENE, 1,1'-METHYLENEBIS [4-ISOCYANATO-

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

| <u>Inventory nat</u> | | |
|-------------------------|---|--|
| Australia | : All components are listed or exempted. | |
| Canada | : All components are listed or exempted. | |
| China | : All components are listed or exempted. | |
| Eurasian Economic Union | : Russian Federation inventory: All components are listed or exempted. | |
| Japan | : Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined. | |
| New Zealand | : All components are listed or exempted. | |
| Philippines | : All components are listed or exempted. | |
| Republic of Korea | : All components are listed or exempted. | |
| Taiwan | : All components are listed or exempted. | |
| Thailand | : All components are listed or exempted. | |
| Turkey | : Not determined. | |
| United States | : All components are active or exempted. | |
| Viet Nam | : All components are listed or exempted. | |

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

12/13

Section 16. Other information



Procedure used to derive the classification

| Classification | | Justification |
|---|---|--------------------|
| ACUTE TOXICITY (inhalation) - Category 4 | | Calculation method |
| SKIN IRRITATION - Category | | Calculation method |
| EYE IRRITATION - Category | 2A | Calculation method |
| RESPIRATORY SENSITIZAT | ΓION - Category 1 | Calculation method |
| SKIN SENSITIZATION - Cate | egory 1 | Calculation method |
| CARCINOGENICITY - Catego | ory 2 | Calculation method |
| SPECIFIC TARGET ORGAN | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract | |
| irritation) - Category 3 | | |
| SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 | | Calculation method |
| <u>History</u> | | |
| Date of printing | : 11/28/2023 | |
| Date of issue/Date of | : 10/20/2022 | |
| revision | | |
| Date of previous issue | : 10/19/2022 | |
| Version | : 1.03 | |
| Key to abbreviations | : ATE = Acute Toxicity Estimate | |

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

References : Not available.

Indicates information that has changed from previously issued version.

N/A = Not available

SGG = Segregation Group UN = United Nations

BCF = Bioconcentration Factor

IBC = Intermediate Bulk Container

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.