

WEICON Cutting Fluid for Stainless Steel



High-performance lubricant | reduces friction and wear | silicone-free

WEICON Cutting Fluid for Stainless Steel is a high-performance lubricant for all types of metalworking, both non-cutting and cutting. It reduces wear on workpieces and tools. It decreases friction and heat generation on metal parts. The transparent special oil extends the service life of cutting tools and drills. Thanks to its high adhesive strength, the pressure-resistant cutting fluid prevents drill tools from slipping and protects surfaces from damage. It increases the efficiency and precision of cutting tools, delivering optimal results. It is permanently temperature-resistant up to +200 °C. It can be used in metalworking for all cutting operations such as drilling, turning, sawing, milling, reaming, threading or punching. The silicone-free spray is suitable for use on stainless steel, all types of steel, copper, aluminium, titanium, brass and cast iron. The drilling and cutting oil can be used in metalworking and many other industrial applications.

Technical data

Odour	mineral oil
Colour	transparent
Specific properties	noise-dampening
Silicone-free	yes
Minimum shelf life	24 mon.
Kinematic viscosity (40°C)	77 mm ² /s
Kinematic viscosity (100°C)	8 mm ² /s
Temperature resistance	-40 °C to +200 °C

Lubricating and Multifunctional Oils

Application

Shake can before use. Spray onto the cleaned and dry surface from a distance of approx. 15 cm. The spray can also be applied again during operation in compliance with the relevant safety regulations.

Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

10105121 WEICON Cutting Fluid for Stainless Steel, 400 ml, transparent

Conversion table

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$
 $\text{mm}/25.4 = \text{inch}$
 $\mu\text{m}/25.4 = \text{mil}$
 $\text{N} \times 0.225 = \text{lb}$
 $\text{N}/\text{mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$

$\text{Nm} \times 8.851 = \text{lb}\cdot\text{in}$
 $\text{Nm} \times 0.738 = \text{lb}\cdot\text{ft}$
 $\text{Nm} \times 141.62 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$
 $\text{N}/\text{cm} \times 0.571 = \text{lb}/\text{in}$
 $\text{kV}/\text{mm} \times 25.4 = \text{V}/\text{mil}$

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr