

Surface and Anti-Corrosion Coating

WEICON Gun Protect

Corrosion protection for firearms, ammunition and metal parts

WEICON Gun Protect is a protective film that permanently coats metal parts with a dry, waxy layer, protecting them from moisture, rust, oxidation and flash rust.

The spray is suitable for protecting metal parts as well as firearms and ammunition – providing reliable, long-lasting protection against rust in gun cabinets, safes or ammunition storage areas.

WEICON Gun Protect is used for the proper, clean and dry storage of all firearms.

If necessary, the protective film can be easily removed (e.g. with WEICON Gun Cleaner).

Complies with Mil-Spec.: MIL-C-16173

Technical data

Odour		solvent
Specific properties		based on wax
Silicone-free		yes
Consumption	per 1.5 crosswise application	~ 2 m ²
Minimum shelf life	at room temperature	24 mon.
Salt spray test	DIN 53167:1985-12	> 500 h
Temperature resistance		-20 °C to +80 °C

Approvals / Guidelines

ISSA Code		53.402.08
IMPA Code		450815
MIL-Spec	complies with	MIL-T-83523

Application

First thoroughly clean the parts to be coated with WEICON Gun Cleaner. Spray WEICON Gun Protect evenly from a distance of 5 cm. The coating will be fully cured at room temperature after approx. 3-4 hours. Several coats can be applied to increase corrosion protection. The protective film can be removed with WEICON Gun Cleaner.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

10105775 WEICON Gun Protect, 400 ml

Conversion table

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$	$\text{Nm} \times 8.851 = \text{lb}\cdot\text{in}$
$\text{mm}/25.4 = \text{inch}$	$\text{Nm} \times 0.738 = \text{lb}\cdot\text{ft}$
$\mu\text{m}/25.4 = \text{mil}$	$\text{Nm} \times 141.62 = \text{oz}\cdot\text{in}$
$\text{N} \times 0.225 = \text{lb}$	$\text{mPa}\cdot\text{s} = \text{cP}$
$\text{N}/\text{mm}^2 \times 145 = \text{psi}$	$\text{N}/\text{cm} \times 0.571 = \text{lb}/\text{in}$
$\text{MPa} \times 145 = \text{psi}$	$\text{kV}/\text{mm} \times 25.4 = \text{V}/\text{mil}$

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr