Elastic adhesives and sealants
MS-Polymers

Special Mixing Nozzle



for Flex 310 M 2 K fast-curing

The special mixing nozzle was specially developed for two-component adhesive systems.

The use of the mixing nozzle supports quality assurance in bonding processes and ensures the reproducibility of results. This is particularly important for industrial series production.

The mixing nozzles support the quality and professional production of adhesive bonds and lead to an improvement in the bonding processes.

The geometry of the mixing nozzle, which is precisely matched to the mixing ratio, ensures that the correct quantities of resin and hardener are mixed together at all times.

The use of the mixing nozzle ensures safe and clean working and increases efficiency by significantly reducing error costs.

Characteristics

Colour		grey
Length		25,5 cm
Mixing ratio		1:1/2:1 MGQ 10-19A
Mixing spirals		19
Tip type		(A)
Minimum shelf life	at room temperature	∞ mon.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Scope of delivery

Special Mixing Nozzle

Suitable for

For Flex 310 M 2 K fast curing.

Conversion table

(°C x 1.8) + 32 = °F	Nm x 8.851 = lb·in
mm/25.4 = inch	Nm x 0.738 = lb·ft
µm/25.4 = mil	Nm x 141.62 = oz·in
N x 0.225 = lb	mPa·s = cP
N/mm^2 x 145 = psi	N/cm x 0.571 = lb/in
MPa x 145 = psi	kV/mm x 25.4 = V/mil

Available sizes

10027692 Special Mixing Nozzle, 1 PCE, grey

To the product detail page:

Note
The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquaters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Colombia S.A.S
Colombia
Phone: +57 314 793 86 06
Email: info@weicon.co

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.L.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr