

# Bike Chain Oil



**special PTFE formula** highly effective white: enables easy visual control

Thanks to its special PTFE formula, the efficient Bike Chain Oil ensures your bike chain and other moving parts on our bike to run extremely smoothly. Ideal for lubrication as well as protection against dirt on the bike chain, sprocket, cassette, rear derailleur, and co. The white oil enables easy visual control of the lubricated areas. Even under heavy use and in wet conditions, the water-repellent chain spray will not let you and your bike down! The Bike Chain Oil is suitable for all types of bicycles: e-bike, mountain bike, gravel bike, racing bike, trekking bike, city bike, Dutch bike, folding bike, and many more.

## Technical Data

Specific properties	with PTFE
Colour	yellow-white
Density	0,93
Temperature resistance	-40 °C to +80 °C
Minimum shelf life	at room temperature 24 mon.

## Approvals / Guidelines

MIL-Spec	complies with	MIL-T-83523
----------	---------------	-------------

## Surface Pre-Treatment

Pretreat drive section and movable components with WEICON Bike Drive Cleaner.

## Application

Apply the Bike Chain Oil evenly to the inside of the clean, dry bike chain, using the Dosing Tip, then turn the crank backwards two to three times to allow the oil to penetrate all spaces between the chain links. Remove excess oil with a dry cloth.

## Storage

Keep tightly closed in original packaging. Protect from direct sunlight. The storage temperature must not exceed +50 °C. Keep container in a cool, well-ventilated place. Store in a dry place.

## Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

## Available sizes

10057748	Bike Chain Oil, 30 ml, yellow-white
10058806	Bike Chain Oil, 30 ml, yellow-white
10060458	Bike Chain Oil, 250 ml, yellow-white
10058970	Bike Chain Oil, 30 ml, yellow-white

## Conversion table

(°C x 1.8) + 32 = °F	Nm x 8.851 = lb·in
mm/25.4 = inch	Nm x 0.738 = lb·ft
µm/25.4 = mil	Nm x 141.62 = oz·in
N x 0.225 = lb	mPa·s = cP
N/mm² x 145 = psi	N/cm x 0.571 = lb/in
MPa x 145 = psi	kV/mm x 25.4 = V/mil

To the product detail page:



## Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
info@weicon.ae

WEICON Inc.  
Canada  
phone +1 877 620 8889  
info@weicon.ca

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
info@weicon.cz

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
info@weicon.es

WEICON GmbH & Co. KG  
(Headquarters) Germany  
phone +49 (0) 251 9322 0  
info@weicon.de

WEICON Italia S.r.l.  
Italy  
phone +39 (0) 010 2924 871  
info@weicon.it

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
office@weicon.com

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
info@weicon.co.za

WEICON South East Asia Pte Ltd  
Singapore  
Phone (+65) 6710 7671  
info@weicon.com.sg

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Türkiye  
phone +90 (0) 212 465 33 65  
info@weicon.com.tr