

Bike Chain Oil



special PTFE formulahighly effectivewhite: enables easy visual control

Thanks to its special PTFE formula, the efficient Bike Chain Oil ensures your bike chain and other moving parts on our bike to run extremely smoothly. Ideal for lubrication as well as protection against dirt on the bike chain, sprocket, cassette, rear derailleur, and co. The white oil enables easy visual control of the lubricated areas. Even under heavy use and in wet conditions, the water-repellent chain spray will not let you and your bike down! The Bike Chain Oil is suitable for all types of bicycles: e-bike, mountain bike, gravel bike, racing bike, trekking bike, city bike, Dutch bike, folding bike, and many more.

Technical Data

Specific properties	with PTFE
Colour	yellow-white
Density	0,93
Temperature resistance	-40 °C to +80 °C
Minimum shelf life	at room temperature 24 mon.

Surface Pre-Treatment

Pretreat drive section and movable components with WEICON Bike Drive Cleaner.

Application

Apply the Bike Chain Oil evenly to the inside of the clean, dry bike chain, using the Dosing Tip, then turn the crank backwards two to three times to allow the oil to penetrate all spaces between the chain links. Remove excess oil with a dry cloth.

Storage

Keep tightly closed in original packaging. Protect from direct sunlight. The storage temperature must not exceed +50 °C. Keep container in a cool, well-ventilated place. Store in a dry place.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

10057748	Bike Chain Oil, 30 ml, yellow-white
10058806	Bike Chain Oil, 30 ml, yellow-white
10060458	Bike Chain Oil, 250 ml, yellow-white
10058970	Bike Chain Oil, 30 ml, yellow-white

Conversion table

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$
 $\text{mm}/25.4 = \text{inch}$
 $\mu\text{m}/25.4 = \text{mil}$
 $\text{N} \times 0.225 = \text{lb}$
 $\text{N}/\text{mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$

$\text{Nm} \times 8.851 = \text{lb}\cdot\text{in}$
 $\text{Nm} \times 0.738 = \text{lb}\cdot\text{ft}$
 $\text{Nm} \times 141.62 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$
 $\text{N}/\text{cm} \times 0.571 = \text{lb}/\text{in}$
 $\text{kV}/\text{mm} \times 25.4 = \text{V}/\text{mil}$

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr