

SAFETY DATA SHEET



WEICON WPN Epoxy Hardener

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : WEICON WPN Epoxy Hardener
UFI : 8A22-80RD-600V-94F1
Product code : 105402
Color : Black.
Product description : Hardener for resins.
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Hardener for resins.

Uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG
Königsberger Str. 255,
48157 Münster, Germany
phone:+49 251 93220,
email: info@weicon.de,
URL: www.weicon.de

e-mail address of person responsible for this SDS : msds@weicon.de

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Corr. 1C, H314

Eye Dam. 1, H318

Skin Sens. 1, H317

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity : 64.8 percent of the mixture consists of component(s) of unknown acute oral toxicity
64.8 percent of the mixture consists of component(s) of unknown acute dermal toxicity
64.8 percent of the mixture consists of component(s) of unknown acute inhalation toxicity

SECTION 2: Hazards identification

Ingredients of unknown ecotoxicity : Contains 64.8% of components with unknown hazards to the aquatic environment

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.

Prevention :

P261 - Avoid breathing vapor.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing and eye or face protection.

Response :

P391 - Collect spillage.
P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor.
P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor.
P363 - Wash contaminated clothing before reuse.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage : P405 - Store locked up.

Disposal : P501 - Dispose of waste according to applicable legislation.

Hazardous ingredients : 2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated; Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine; 3-aminomethyl-3,5,5-trimethylcyclohexylamine; m-phenylenebis(methylamine); 2,4,6-tris(dimethylaminomethyl)phenol; Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols; benzyl alcohol; 2-piperazin-1-ylethylamine; 3-aminopropyltriethoxysilane and 3-aminopropyltriethoxysilane

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Yes, applicable.

Tactile warning of danger : Yes, applicable.

WEICON WPN Epoxy Hardener

SECTION 2: Hazards identification

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino] butyl-terminated	CAS: 68683-29-4	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	REACH #: 01-2119983521-35 EC: 606-078-8 CAS: 186321-96-0	≥5 - ≤10	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6	≥3 - ≤5	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	ATE [Oral] = 1620 mg/kg ATE [Inhalation (dusts and mists)] = 4.178 mg/l	[1] [2]
3-aminomethyl-3,5,5-trimethylcyclohexylamine	REACH #: 01-2119514687-32 EC: 220-666-8 CAS: 2855-13-2 Index: 612-067-00-9	≥1 - ≤3	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	ATE [Oral] = 1030 mg/kg Skin Sens. 1, H317: C ≥ 0.001%	[1] [2]
m-phenylenebis (methylamine)	REACH #: 01-2119480150-50 EC: 216-032-5 CAS: 1477-55-0	≥1 - ≤1.6	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412 EUH071	ATE [Oral] = 930 mg/kg ATE [Inhalation (dusts and mists)] = 1.34 mg/l	[1] [2]
2,4,6-tris (dimethylaminomethyl) phenol	EC: 202-013-9 CAS: 90-72-2	≥1 - ≤2.4	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318	ATE [Oral] = 500 mg/kg	[1]
Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols	-	≥1 - ≤3	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥0.3 - <1	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317	ATE [Oral] = 1200 mg/kg	[1] [2]

SECTION 3: Composition/information on ingredients

2-piperazin-1-ylethylamine	REACH #: 01-2119471486-30 EC: 205-411-0 CAS: 140-31-8	≥0.3 - <1	Acute Tox. 4, H302 Acute Tox. 3, H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361 STOT RE 1, H372 Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/kg ATE [Dermal] = 300 mg/kg	[1]
3-aminopropyltriethoxysilane	REACH #: 01-2119480479-24 EC: 213-048-4 CAS: 919-30-2	≥0.3 - <1	Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317	ATE [Inhalation (vapours)] = 11 mg/l Skin Sens. 1, H317: C ≥ 3%	[1]
3-aminopropyltriethoxysilane	REACH #: 01-2119480479-24 EC: 213-048-4 CAS: 919-30-2	≥0.1 - ≤0.3	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317	ATE [Oral] = 1491 mg/kg	[1]
octamethylcyclotetrasiloxane	EC: 209-136-7 CAS: 556-67-2	<0.01	Flam. Liq. 3, H226 Repr. 2, H361f Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	M [Chronic] = 10	[1] [3] [4]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a physical, health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

SECTION 4: First aid measures

- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

SECTION 5: Firefighting measures

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

SECTION 7: Handling and storage

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
E2	200 tonnes	500 tonnes

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
benzyl alcohol	<p>DFG MAC-values list (Germany, 7/2024) Develop C. Absorbed through skin. PEAK 15 minutes: 44 mg/m³ 4 times per shift [Interval: 1 hour]. PEAK 15 minutes: 10 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 22 mg/m³. TWA 8 hours: 5 ppm.</p> <p>TRGS 900 OEL (Germany, 3/2025) Absorbed through skin. PEAK 15 minutes: 10 ppm. PEAK 15 minutes: 44 mg/m³. TWA 8 hours: 22 mg/m³. TWA 8 hours: 5 ppm.</p>
3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine) benzyl alcohol	<p>DFG MAC-values list (Germany, 7/2024) Skin sensitizer. DFG MAC-values list (Germany, 7/2024) Skin sensitizer. DFG MAC-values list (Germany, 7/2024) Develop C. Absorbed through skin. PEAK 15 minutes: 44 mg/m³ 4 times per shift [Interval: 1 hour]. PEAK 15 minutes: 10 ppm 4 times per shift [Interval: 1 hour].</p>

SECTION 8: Exposure controls/personal protection

TWA 8 hours: 22 mg/m³.
 TWA 8 hours: 5 ppm.
TRGS 900 OEL (Germany, 3/2025) Absorbed through skin.
 PEAK 15 minutes: 10 ppm.
 PEAK 15 minutes: 44 mg/m³.
 TWA 8 hours: 22 mg/m³.
 TWA 8 hours: 5 ppm.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following:
 European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine

Result

DNEL - General population - Long term - Oral

0.5 mg/kg bw/day
Effects: Systemic

DNEL - General population - Long term - Dermal

0.5 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Long term - Dermal

1 mg/kg bw/day
Effects: Systemic

DNEL - General population - Long term - Inhalation

1.74 mg/m³
Effects: Systemic

DNEL - Workers - Long term - Inhalation

7.05 mg/m³
Effects: Systemic

benzyl alcohol

DNEL - General population - Long term - Oral

4 mg/kg bw/day
Effects: Systemic

DNEL - General population - Long term - Dermal

4 mg/kg bw/day
Effects: Systemic

DNEL - General population - Long term - Inhalation

5.4 mg/m³
Effects: Systemic

DNEL - Workers - Long term - Dermal

8 mg/kg bw/day
Effects: Systemic

DNEL - General population - Short term - Oral

20 mg/kg bw/day

SECTION 8: Exposure controls/personal protection

Effects: Systemic

DNEL - General population - Short term - Dermal

20 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

22 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

27 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Dermal

40 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Inhalation

110 mg/m³

Effects: Systemic

3-aminomethyl-
3,5,5-trimethylcyclohexylamine

DNEL - Workers - Short term - Inhalation

0.073 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

0.073 mg/m³

Effects: Local

DNEL - General population - Long term - Oral

0.3 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Oral

0.3 mg/kg bw/day

Effects: Systemic

m-phenylenebis(methylamine)

DNEL - Workers - Long term - Inhalation

0.2 mg/m³

Effects: Local

DNEL - Workers - Long term - Dermal

0.33 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

1.2 mg/m³

Effects: Systemic

2,4,6-tris(dimethylaminomethyl)phenol

DNEL - General population - Long term - Oral

0.075 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

0.075 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

0.075 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Inhalation

SECTION 8: Exposure controls/personal protection

0.13 mg/m³
Effects: Systemic

DNEL - General population - Long term - Inhalation
0.13 mg/m³
Effects: Systemic

DNEL - Workers - Long term - Dermal
0.15 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Long term - Inhalation
0.53 mg/m³
Effects: Systemic

DNEL - Workers - Short term - Dermal
0.6 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Short term - Inhalation
2.1 mg/m³
Effects: Systemic

benzyl alcohol

DNEL - General population - Long term - Oral
4 mg/kg bw/day
Effects: Systemic

DNEL - General population - Long term - Dermal
4 mg/kg bw/day
Effects: Systemic

DNEL - General population - Long term - Inhalation
5.4 mg/m³
Effects: Systemic

DNEL - Workers - Long term - Dermal
8 mg/kg bw/day
Effects: Systemic

DNEL - General population - Short term - Oral
20 mg/kg bw/day
Effects: Systemic

DNEL - General population - Short term - Dermal
20 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Long term - Inhalation
22 mg/m³
Effects: Systemic

DNEL - General population - Short term - Inhalation
27 mg/m³
Effects: Systemic

DNEL - Workers - Short term - Dermal
40 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Short term - Inhalation
110 mg/m³
Effects: Systemic

SECTION 8: Exposure controls/personal protection

2-piperazin-1-ylethylamine

DNEL - Workers - Long term - Inhalation

15 µg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

80 µg/m³

Effects: Local

DNEL - Workers - Long term - Dermal

3.33 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Inhalation

10.6 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

10.6 mg/m³

Effects: Systemic

3-aminopropyltriethoxysilane

DNEL - General population - Long term - Oral

1 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

1 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

3.5 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

14 mg/m³

Effects: Systemic

3-aminopropyltriethoxysilane

DNEL - General population - Long term - Oral

1 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

1 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

3.5 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

14 mg/m³

Effects: Systemic

octamethylcyclotetrasiloxane

DNEL - General population - Long term - Oral

3.7 mg/kg bw/day

Effects: Systemic

SECTION 8: Exposure controls/personal protection

DNEL - General population - Long term - Inhalation

13 mg/m³

Effects: Local

DNEL - General population - Long term - Inhalation

13 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

73 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

73 mg/m³

Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): Protective gloves made of nitrile rubber (material thickness of 0,4 mm); EN 374-5 Cat. III ; 4 - 8 hours (breakthrough time): Protective gloves made of Viton®/ butyl rubber (material thickness of 0,7 mm); EN388 Cat.II / EN374 Cat.III / EN374-2

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter

SECTION 8: Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Color : Black.
Odor : Characteristic.
Odor threshold : Not available.
Melting point/freezing point : Not available.
Boiling point or initial boiling point and boiling range : Not available.
Flammability : Not available.
Lower and upper explosion limit : Not available.
Flash point :

Ingredient name	Closed cup			Open cup		
	°C	°F	Method	°C	°F	Method
octamethylcyclotetrasiloxane	56	132.8				
decamethylcyclopentasiloxane				82.7	180.9	ASTM D 3828-87
3-aminopropyltriethoxysilane	93	199.4	DIN 51758			
3-aminopropyltriethoxysilane	93	199.4	DIN 51758			
2-piperazin-1-ylethylamine				99	210.2	ISO 2719
benzyl alcohol	100.56	213				
benzyl alcohol	100.56	213				
3-aminomethyl-3,5,5-trimethylcyclohexylamine				110	230	
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	>110	>230				
m-phenylenebis(methylamine)				134	273.2	

Auto-ignition temperature :

Ingredient name	°C	°F	Method
2-piperazin-1-ylethylamine	>300	>572	
decamethylcyclopentasiloxane	372	701.6	ASTM E 659-78
2,4,6-tris(dimethylaminomethyl)phenol	382	719.6	EU A.15
octamethylcyclotetrasiloxane	384 to 387	723.2 to 728.6	ASTM E 659
benzyl alcohol	436	816.8	
benzyl alcohol	436	816.8	

Decomposition temperature : Not available.

pH : Not applicable.

SECTION 9: Physical and chemical properties

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): Not available.

Solubility :
Not available.

Solubility in water : Not available.

Partition coefficient n-octanol/ water (log Pow) : Not applicable.

Vapor pressure :

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
octamethylcyclotetrasiloxane	0.99008	0.13				
decamethylcyclopentasiloxane	0.25	0.033				
2,4,6-tris(dimethylaminomethyl) phenol	0.056	0.0075	EU A.4			
benzyl alcohol	0.05	0.0067				
benzyl alcohol	0.05	0.0067				
2-piperazin-1-ylethylamine	0.039	0.0052				
3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.01178	0.0016	OECD 104			
m-phenylenebis(methylamine)	0.0052	0.00069	OECD 104			

Relative density : Not available.

Density : 2.2 g/cm³ [20°C (68°F)]

Relative vapor density : Not available.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

Oxidizing properties : Not available.

9.2.2 Other safety characteristics

Miscible with water : No.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

benzyl alcohol

Result

Rat - Oral - LD50

1230 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Excitement Behavioral - Coma

Rabbit - Dermal - LD50

2000 mg/kg

m-phenylenebis(methylamine)

Rat - Oral - LD50

930 mg/kg

Rabbit - Dermal - LD50

2 g/kg

Rat - Inhalation - LC50 Gas.

700 ppm [1 hours]

Toxic effects: Eye - Lacrimation Lung, Thorax, or Respiration - Respiratory depression

benzyl alcohol

Rat - Oral - LD50

1230 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Excitement Behavioral - Coma

Mouse - Oral - LD50

1360 mg/kg

Rabbit - Oral - LD50

1040 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity)

Mouse - Oral - LD50

1360 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

Rat - Oral - LD50

1660 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

Rabbit - Oral - LD50

1040 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

Rabbit - Dermal - LD50

2000 mg/kg

Rat - Oral - LD50

1.5 ml/kg

3-aminopropyltriethoxysilane

Rat - Oral - LD50

1.57 g/kg

Toxic effects: Gastrointestinal - Hypermotility, diarrhea Kidney,

SECTION 11: Toxicological information

Ureter, and Bladder - Changes in tubules (including acute renal failure, acute tubular necrosis)

Rabbit - Dermal - LD50

4.29 g/kg

Toxic effects: Gastrointestinal - Ulceration or bleeding from stomach Kidney, Ureter, and Bladder - Other changes Skin After topical exposure - Primary irritation

3-aminopropyltriethoxysilane

Rabbit - Dermal - LD50

4.29 g/kg

Toxic effects: Gastrointestinal - Ulceration or bleeding from stomach Kidney, Ureter, and Bladder - Other changes Skin After topical exposure - Primary irritation

Rat - Oral - LD50

1.57 g/kg

Toxic effects: Gastrointestinal - Hypermotility, diarrhea Kidney, Ureter, and Bladder - Changes in tubules (including acute renal failure, acute tubular necrosis)

octamethylcyclotetrasiloxane

Rat - Inhalation - LC50 Vapor

36 g/m³ [4 hours]

Toxic effects: Behavioral - Excitement Lung, Thorax, or Respiration - Dyspnea Other - Hair

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
WEICON WPN Epoxy Hardener	3689.8	20068.3	N/A	N/A	16.9
benzyl alcohol	1620	N/A	N/A	N/A	4.178
3-aminomethyl-3,5,5-trimethylcyclohexylamine	1030	N/A	N/A	N/A	N/A
m-phenylenebis(methylamine)	930	N/A	N/A	N/A	1.34
2,4,6-tris(dimethylaminomethyl)phenol	500	N/A	N/A	N/A	N/A
benzyl alcohol	1200	N/A	N/A	N/A	N/A
2-piperazin-1-ylethylamine	500	300	N/A	N/A	N/A
3-aminopropyltriethoxysilane	N/A	4290	N/A	11	N/A
3-aminopropyltriethoxysilane	1491	4290	N/A	N/A	N/A
octamethylcyclotetrasiloxane	N/A	N/A	N/A	36	N/A

Skin corrosion/irritation

Product/ingredient name

benzyl alcohol

Result

Man - Skin - Mild irritant

Duration of treatment/exposure: 48 hours

Amount/concentration applied: 16 mg

Pig - Skin - Moderate irritant

Amount/concentration applied: 100 %

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

m-phenylenebis(methylamine)

Rabbit - Skin - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 750 ug

SECTION 11: Toxicological information

benzyl alcohol

Man - Skin - Mild irritant

Duration of treatment/exposure: 48 hours

Amount/concentration applied: 16 mg

Pig - Skin - Moderate irritant

Amount/concentration applied: 100 %

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

2-piperazin-1-ylethylamine

Rabbit - Skin - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

3-aminopropyltriethoxysilane

Rabbit - Skin - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

3-aminopropyltriethoxysilane

Rabbit - Skin - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

m-phenylenebis(methylamine)

Result

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 50 ug

2-piperazin-1-ylethylamine

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

3-aminopropyltriethoxysilane

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 750 ug

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
2-piperazin-1-ylethylamine	STOT RE 1, H372

Aspiration hazard

Not available.

Information on the likely routes of exposure

Not available.

Potential acute health effects

Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

SECTION 11: Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

benzyl alcohol

Result

Acute - LC50 - Fresh water

Fish - Bluegill - *Lepomis macrochirus*
10 ppm [96 hours]
Effect: Mortality

3-aminomethyl-
3,5,5-trimethylcyclohexylamine

Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*
Age: <24 hours
17.4 mg/l [48 hours]
Effect: Intoxication

benzyl alcohol

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas* - Juvenile (Fledgling, Hatchling, Weanling)
Age: 4 to 8 weeks; Size: 1.1 to 3.1 cm
460 mg/l [96 hours]
Effect: Mortality

Acute - LC50 - Fresh water

Fish - Bluegill - *Lepomis macrochirus*
10 ppm [96 hours]
Effect: Mortality

2-piperazin-1-ylethylamine

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*
Age: 31 days; Size: 21 mm; Weight: 0.147 g
2190 mg/l [96 hours]
Effect: Mortality

octamethylcyclotetrasiloxane

Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*
Age: <24 hours
7.9 µg/l [21 days]

SECTION 12: Ecological information

Effect: Mortality

Chronic - NOEC

STDMETH

Algae - Green algae - *Selenastrum capricornutum*

1 to 29 µg/l [96 hours]

Effect: Population

Chronic - NOEC - Fresh water

Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss* - Embryo

Age: ≤24 hours

4.4 µg/l [33 days]

Effect: Mortality

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
benzyl alcohol	0.87	-	Low
3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.99	-	Low
m-phenylenebis(methylamine)	0.18	2.69	Low
2,4,6-tris(dimethylaminomethyl)phenol	0.219	-	Low
benzyl alcohol	0.87	-	Low
2-piperazin-1-ylethylamine	-1.48	-	Low
3-aminopropyltriethoxysilane	1.7	3.4 [OECD 305 C]	Low
3-aminopropyltriethoxysilane	1.7	3.4 [OECD 305 C]	Low
octamethylcyclotetrasiloxane	6.488	13400 [EPA OTS 797.1520]	High

12.4 Mobility in soil

Soil/Water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
benzyl alcohol	1.1	12.6442
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2	98.3852
m-phenylenebis(methylamine)	1.7	46.5812
2,4,6-tris(dimethylaminomethyl)phenol	2.7	525.589
benzyl alcohol	1.1	12.6442
2-piperazin-1-ylethylamine	1.5	33.6814
3-aminopropyltriethoxysilane	2.5	282.955
3-aminopropyltriethoxysilane	2.5	282.955
octamethylcyclotetrasiloxane	3.5	3064.9

Results of PMT and vPvM assessment

SECTION 12: Ecological information

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino] butyl-terminated	No	No	No	No	No	No	No
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	No	No	No	No	No	No	No
benzyl alcohol	No	No	No	No	No	No	No
3-aminomethyl-3,5,5-trimethylcyclohexylamine	No	No	No	No	No	No	No
m-phenylenebis(methylamine)	No	No	No	No	No	No	No
2,4,6-tris(dimethylaminomethyl)phenol	No	No	No	No	No	No	No
Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols	No	No	No	No	No	No	No
benzyl alcohol	No	No	No	No	No	No	No
2-piperazin-1-ylethylamine	No	No	No	No	No	No	No
3-aminopropyltriethoxysilane	No	No	No	No	No	No	No
3-aminopropyltriethoxysilane	No	No	No	No	No	No	No
octamethylcyclotetrasiloxane	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino] butyl-terminated	No	N/A	N/A	No	N/A	N/A	N/A
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	No	N/A	N/A	No	N/A	N/A	N/A
benzyl alcohol	No	N/A	N/A	No	N/A	N/A	N/A
3-aminomethyl-3,5,5-trimethylcyclohexylamine	No	N/A	N/A	No	N/A	N/A	N/A
m-phenylenebis(methylamine)	No	N/A	No	No	No	N/A	No
2,4,6-tris(dimethylaminomethyl)phenol	No	N/A	N/A	No	N/A	N/A	N/A
Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols	No	N/A	N/A	No	N/A	N/A	N/A
benzyl alcohol	No	N/A	N/A	No	N/A	N/A	N/A
2-piperazin-1-ylethylamine	N/A	N/A	N/A	Yes	N/A	N/A	N/A
3-aminopropyltriethoxysilane	No	N/A	No	No	No	N/A	No
3-aminopropyltriethoxysilane	No	N/A	No	No	No	N/A	No
octamethylcyclotetrasiloxane	Yes	Yes	Yes	Yes	Yes	Yes	Yes

SECTION 12: Ecological information

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	No	No	No	No	No	No	No
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	No	No	No	No	No	No	No
benzyl alcohol	No	No	No	No	No	No	No
3-aminomethyl-3,5,5-trimethylcyclohexylamine	No	No	No	No	No	No	No
m-phenylenebis(methylamine)	No	No	No	No	No	No	No
2,4,6-tris(dimethylaminomethyl)phenol	No	No	No	No	No	No	No
Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols	No	No	No	No	No	No	No
benzyl alcohol	No	No	No	No	No	No	No
2-piperazin-1-ylethylamine	No	No	No	No	No	No	No
3-aminopropyltriethoxysilane	No	No	No	No	No	No	No
3-aminopropyltriethoxysilane	No	No	No	No	No	No	No
octamethylcyclotetrasiloxane	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

SECTION 13: Disposal considerations

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Can	15 01 10* packaging containing residues of or contaminated by hazardous substances

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1760	UN1760	UN1760	UN1760
14.2 UN proper shipping name	CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))	CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))	CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))	CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))
14.3 Transport hazard class(es)	8  	8  	8  	8 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information

ADR/RID : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Tunnel code (E)

ADN : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed above the relevant limit.

Substances of very high concern

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
PBT	octamethylcyclotetrasiloxane	Recommended	10th recommendation	4/14/2021
vPvB	octamethylcyclotetrasiloxane	Recommended	10th recommendation	4/14/2021

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
WEICON WPN Epoxy Hardener	≥90	3

Labeling : Not applicable.

Synthetic polymer microparticles - Designation 78

Generic identity of polymer(s) : Not applicable.

Total percentage of synthetic polymer microparticles : Not applicable.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
E2

Annex VIIA - Labelling for Contents

Identification

BENZYL ALCOHOL
BENZYL ALCOHOL

Concentration

less than 5%
less than 5%

SECTION 15: Regulatory information

VOC content : 1.8 %

VOC (g/L) : 39.75

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
benzyl alcohol	DFG MAC-values list	-	Develop C	-
benzyl alcohol	DFG MAC-values list	-	Develop C	-

Storage class (TRGS 510) : 8B

Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

Danger criteria

Category	Reference number
E2	1.3.2

Hazard class for water : 3

Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
5.2.1	Total dust	77.7
5.2.5	Organic substances	20.4
5.2.5 [I]	Organic substances	6

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: Not determined.
Canada	: Not determined.
China	: Not determined.
Eurasian Economic Union	: Russian Federation inventory : Not determined.
Japan	: Japan inventory (CSCL) : Not determined. Japan inventory (ISHL) : Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: Not determined.

WEICON WPN Epoxy Hardener

SECTION 15: Regulatory information

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- B = Bioaccumulative
- BCF = Bioconcentration Factor
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- IATA = International Air Transport Association
- IMDG = International Maritime Dangerous Goods
- IMO = International Maritime Organization
- M = Mobile
- N/A = Not available
- P = Persistent
- PBT = Persistent, Bioaccumulative and Toxic
- PMT = Persistent, Mobile and Toxic
- PNEC = Predicted No Effect Concentration
- RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
- RRN = REACH Registration Number
- SGG = Segregation Group
- T = Toxic
- vB = Very Bioaccumulative
- vM = Very Mobile
- vP = Very Persistent
- vPvB = Very Persistent and Very Bioaccumulative
- vPvM = Very Persistent and Very Mobile

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Corr. 1C, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361	Suspected of damaging fertility or the unborn child.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

WEICON WPN Epoxy Hardener

SECTION 16: Other information

[Full text of classifications \[CLP/GHS\]](#)

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	TOXIC TO REPRODUCTION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1A	SKIN SENSITIZATION - Category 1A
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Date of printing : 05/02/2026

Date of issue/ Date of revision : 29/01/2026

Date of previous issue : 13/11/2025

Version : 1.8

[Notice to reader](#)

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.