

SAFETY DATA SHEET



Urethane 85-SF Hardener

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Urethane 85-SF Hardener
UFI : JYR1-30H3-T00W-6WX0
Product code : 108522
Color : Yellowish.
Product description : Hardener for resins.
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Hardener for resins.

Uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG
Königsberger Str. 255,
48157 Münster, Germany
phone:+49 251 93220,
email: info@weicon.de,
URL: www.weicon.de

e-mail address of person responsible for this SDS : msds@weicon.de

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319
Resp. Sens. 1, H334
Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity : 2.3 percent of the mixture consists of component(s) of unknown acute oral toxicity
2.3 percent of the mixture consists of component(s) of unknown acute dermal toxicity
2.3 percent of the mixture consists of component(s) of unknown acute inhalation toxicity

SECTION 2: Hazards identification

Ingredients of unknown ecotoxicity : Contains 2.3% of components with unknown hazards to the aquatic environment

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.

Prevention :

P261 - Avoid breathing vapor.
P264 - Wash thoroughly after handling.
P280 - Wear protective gloves. Wear eye or face protection.
P284 - Wear respiratory protection.

Response :

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor.
P362 + P364 - Take off contaminated clothing and wash it before reuse.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage : Not applicable.

Disposal : P501 - Dispose of waste according to applicable legislation.

Hazardous ingredients : Aromatic. Polyisocyanate Prepolymer; 4-isocyanatosulphonyltoluene; hexahydro-4-methylphthalic anhydride and m-tolylidene diisocyanate

Supplemental label elements : Contains isocyanates. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Yes, applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Urethane 85-SF Hardener

SECTION 2: Hazards identification

Other hazards which do not result in classification : May cause endocrine disruption.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Aromatic. Polyisocyanate Prepolymer	CAS: 37273-56-6	≥90	Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
4-isocyanatosulphonyltoluene	REACH #: 01-2119980050-47 EC: 223-810-8 CAS: 4083-64-1 Index: 615-012-00-7	≥1 - ≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 STOT SE 3, H335 EUH014	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5% STOT SE 3, H335: C ≥ 5%	[1]
hexahydro-4-methylphthalic anhydride	REACH #: 01-2119510879-29 EC: 243-072-0 CAS: 19438-60-9 Index: 607-241-00-6	≥0.3 - <1	Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317	-	[1] [3]
m-tolyldiene diisocyanate	REACH #: 01-2119454791-34 EC: 247-722-4 CAS: 26471-62-5 Index: 615-006-00-4	<0.1	Acute Tox. 1, H330 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above.	ATE [Inhalation (vapours)] = 0.107 mg/l Resp. Sens. 1, H334: C ≥ 0.1%	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

SECTION 4: First aid measures

- waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or symptoms, avoid further exposure.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
wheezing and breathing difficulties
asthma
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.

SECTION 5: Firefighting measures

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
Hydrogen cyanide (HCN).

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Urethane 85-SF Hardener

SECTION 7: Handling and storage

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
m-tolyldiene diisocyanate	<p>DFG MAC-values list (Germany, 7/2024) [Toluene diisocyanate] Develop C. Inhalation sensitizer , Skin sensitizer. PEAK 15 minutes: 0.007 mg/m³ 4 times per shift [Interval: 1 hour]. PEAK 15 minutes: 0.001 ppm 4 times per shift [Interval: 1 hour]. CEIL: 0.035 mg/m³. CEIL: 0.005 ml/m³. TWA 8 hours: 0.007 mg/m³. TWA 8 hours: 0.001 ppm.</p> <p>EU OEL (Europe, 3/2024) [diisocyanates] Absorbed through skin , Skin sensitizer , Inhalation sensitizer. STEL 15 minutes: 20 µg/m³ (as isocyanates functional groups of the diisocyanate compounds.). TWA 8 hours: 10 µg/m³ (as isocyanates functional groups of the diisocyanate compounds.).</p>

Biological exposure indices

Product/ingredient name	Exposure indices
m-tolyldiene diisocyanate	<p>DFG BEI-values list (Germany, 7/2024) BEI: 5 µg/g creatinine, sum of 2,4- and 2,6-TDA (after hydrolysis) [in urine]. Sampling time: end of exposure or end of shift.</p>

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

4-isocyanatosulphonyltoluene

Result

DNEL - General population - Long term - Oral

0.46 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

0.46 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.8 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.92 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

3.24 mg/m³

Effects: Systemic

octamethylcyclotetrasiloxane

DNEL - General population - Long term - Oral

3.7 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

13 mg/m³

Effects: Local

DNEL - General population - Long term - Inhalation

13 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

73 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

73 mg/m³

Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : ; Viton® , Butyl rubber gloves.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : inorganic gases/vapors filter (Type B)

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Color : Yellowish.

Odor : Odorless.

Odor threshold : Not available.

Melting point/freezing point : Not available.

Boiling point or initial boiling point and boiling range : Not available.

Flammability : Not available.

Lower and upper explosion limit : Not available.

Flash point : Closed cup: 190°C (374°F)

Auto-ignition temperature :

Urethane 85-SF Hardener

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
decamethylcyclopentasiloxane	372	701.6	ASTM E 659-78
octamethylcyclotetrasiloxane	384 to 387	723.2 to 728.6	ASTM E 659
m-tolylidene diisocyanate	>595	>1103	EU A.15

Decomposition temperature : Not available.
pH : Not applicable.
Viscosity : Dynamic: 7000 mPa·s
Solubility :
 Not available.

Solubility in water : Not available.
Partition coefficient n-octanol/ water (log Pow) : Not applicable.
Vapor pressure :

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
octamethylcyclotetrasiloxane	0.99	0.13	EU A.4			
decamethylcyclopentasiloxane	0.25	0.033				
m-tolylidene diisocyanate	0.01	0.0013				
4-isocyanatosulphonyltoluene	0.00019	0.000025				
hexahydro-4-methylphthalic anhydride	0	0				
tosyl chloride	0	0				

Relative density : Not available.
Density : 1.1 g/cm³ [20°C (68°F)]
Relative vapor density : Not available.
Particle characteristics
Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.
Oxidizing properties : Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability : The product is stable.
10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid : No specific data.
10.5 Incompatible materials : No specific data.

Urethane 85-SF Hardener

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Reactive or incompatible with the following materials: oxidizing materials, acids and alkalis.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

4-isocyanatosulphonyltoluene

Result

Rat - Oral - LD50

2234 mg/kg

Toxic effects: Gastrointestinal - Other changes

m-tolylidene diisocyanate

Rat - Oral - LD50

4130 mg/kg

Rat - Male, Female - Inhalation - LC50 Vapor

0.107 mg/l [4 hours]

OECD 403

Rat - Inhalation - LC50 Dusts and mists

107 mg/m³ [4 hours]

octamethylcyclotetrasiloxane

Rat - Inhalation - LC50 Vapor

36 g/m³ [4 hours]

Toxic effects: Behavioral - Excitement Lung, Thorax, or Respiration - Dyspnea Other - Hair

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
4-isocyanatosulphonyltoluene	2234	N/A	N/A	N/A	N/A
m-tolylidene diisocyanate	4130	N/A	N/A	0.107	N/A

Skin corrosion/irritation

Product/ingredient name

4-isocyanatosulphonyltoluene

Result

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 uL

m-tolylidene diisocyanate

Rabbit - Skin - Severe irritant

Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

4-isocyanatosulphonyltoluene

Result

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 uL

Conclusion/Summary [Product] : Not available.

SECTION 11: Toxicological information

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
4-isocyanatosulphonyltoluene	-
m-tolylidene diisocyanate	-

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
 - pain or irritation
 - watering
 - redness

SECTION 11: Toxicological information

Inhalation : Adverse symptoms may include the following:
wheezing and breathing difficulties
asthma

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : May cause endocrine disruption.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

octamethylcyclotetrasiloxane

Result

Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*

Age: <24 hours

7.9 µg/l [21 days]

Effect: Mortality

Chronic - NOEC

STDMETH

Algae - Green algae - *Selenastrum capricornutum*

1 to 29 µg/l [96 hours]

Effect: Population

Chronic - NOEC - Fresh water

Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss* - Embryo

Age: ≤24 hours

4.4 µg/l [33 days]

Effect: Mortality

Conclusion/Summary [Product] : Not available.

Urethane 85-SF Hardener

SECTION 12: Ecological information

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
hexahydro-4-methylphthalic anhydride	2.09	-	Low
m-tolylidene diisocyanate	3.43	-	Low

12.4 Mobility in soil

Soil/Water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
4-isocyanatosulphonyltoluene	1.5	31.6836
octamethylcyclotetrasiloxane	3.5	3064.9

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Aromatic. Polyisocyanate Prepolymer	No	No	No	No	No	No	No
4-isocyanatosulphonyltoluene	No	No	No	No	No	No	No
hexahydro-4-methylphthalic anhydride	No	No	No	No	No	No	No
m-tolylidene diisocyanate	No	No	No	No	No	No	No
octamethylcyclotetrasiloxane	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Aromatic. Polyisocyanate Prepolymer	No	N/A	N/A	No	N/A	N/A	N/A
4-isocyanatosulphonyltoluene	No	N/A	N/A	No	N/A	N/A	N/A
hexahydro-4-methylphthalic anhydride	No	N/A	N/A	No	N/A	N/A	N/A
m-tolylidene diisocyanate	No	N/A	N/A	No	N/A	N/A	N/A
octamethylcyclotetrasiloxane	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Aromatic. Polyisocyanate Prepolymer	No	No	No	No	No	No	No
4-isocyanatosulphonyltoluene	No	No	No	No	No	No	No
hexahydro-4-methylphthalic anhydride	No	No	No	No	No	No	No
m-tolylidene diisocyanate	No	No	No	No	No	No	No
octamethylcyclotetrasiloxane	No	No	No	No	No	No	No

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.

Regulation (EC) No. 1272/2008 [CLP]

Urethane 85-SF Hardener

SECTION 12: Ecological information

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 05 01*	waste isocyanates

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Can	15 01 10* packaging containing residues of or contaminated by hazardous substances

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not available.	Not available.	Not available.	Not available.
14.2 UN proper shipping name	Not available.	Not available.	Not available.	Not available.
14.3 Transport hazard class(es)	Not available.	Not available.	Not available.	Not available.
14.4 Packing group	-	-	-	-

Urethane 85-SF Hardener

SECTION 14: Transport information

14.5 Environmental hazards	No.	No.	No.	No.
-----------------------------------	-----	-----	-----	-----

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorization](#)

[Annex XIV](#)

None of the components are listed above the relevant limit.

[Substances of very high concern](#)

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
Substance of equivalent concern for human health	hexahydromethylphthalic anhydride [The individual isomers [2], [3] and [4] (including their cis- and trans- stereo isomeric forms) and all possible combinations of the isomers [1] are covered by this entry]	Recommended	ED/01/2018	10/1/2019
Endocrine disrupting properties for human health	hexahydromethylphthalic anhydride [The individual isomers [2], [3] and [4] (including their cis- and trans- stereo isomeric forms) and all possible combinations of the isomers [1] are covered by this entry]	Recommended	ED/01/2018	10/1/2019

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

Product/ingredient name	%	Designation [Usage]
FastRep Putty Hardener	≥90	3

Labeling : Not applicable.

[Synthetic polymer microparticles - Designation 78](#)

Generic identity of polymer(s) : Not applicable.

Total percentage of synthetic polymer microparticles : Not applicable.

[Other EU regulations](#)

Industrial emissions (integrated pollution prevention and control) - Air : Listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Urethane 85-SF Hardener

SECTION 15: Regulatory information

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

VOC content : 0.016 %

VOC (g/L) : 0.171

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
m-tolylidene diisocyanate	DFG MAC-values list	Toluene diisocyanate	Develop C	-

Storage class (TRGS 510) : 10

Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water : 1

Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
5.2.1	Total dust	0.0094
5.2.5	Organic substances	95.7
5.2.5 [I]	Organic substances	1.6

AOX : The product contains organically bound halogens and can contribute to the AOX value in waste water.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: Not determined.
Canada	: Not determined.
China	: Not determined.
Eurasian Economic Union	: Russian Federation inventory : Not determined.
Japan	: Japan inventory (CSCL) : Not determined. Japan inventory (ISHL) : Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.

Urethane 85-SF Hardener

SECTION 15: Regulatory information

Thailand	: Not determined.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: Not determined.

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate B = Bioaccumulative BCF = Bioconcentration Factor CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods IMO = International Maritime Organization M = Mobile N/A = Not available P = Persistent PBT = Persistent, Bioaccumulative and Toxic PMT = Persistent, Mobile and Toxic PNEC = Predicted No Effect Concentration RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SGG = Segregation Group T = Toxic vB = Very Bioaccumulative vM = Very Mobile vP = Very Persistent vPvB = Very Persistent and Very Bioaccumulative vPvM = Very Persistent and Very Mobile
-----------------------------------	--

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317	Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.
EUH014	Reacts violently with water.

Full text of classifications [CLP/GHS]

Urethane 85-SF Hardener

SECTION 16: Other information

Acute Tox. 1	ACUTE TOXICITY - Category 1
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Resp. Sens. 1	RESPIRATORY SENSITIZATION - Category 1
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Date of printing : 05/02/2026

Date of issue/ Date of revision : 29/01/2026

Date of previous issue : 04/11/2025

Version : 5.8

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.