

SAFETY DATA SHEET



Activator F Liquid

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Activator F Liquid
UFI : 7JU1-9071-000S-15DX
Product code : 307002
Color : Green.
Product description : Activators-Surface treatment products
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Activators-Surface treatment products

Uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG
Königsberger Str. 255,
48157 Münster, Germany
phone:+49 251 93220,
email: info@weicon.de,
URL: www.weicon.de

e-mail address of person responsible for this SDS : msds@weicon.de

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225
Eye Irrit. 2, H319
STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Activator F Liquid

SECTION 2: Hazards identification

Hazard pictograms



Signal word

: Danger

Hazard statements

: H225 - Highly flammable liquid and vapor.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements

General

: P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.

Prevention

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing vapor.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye or face protection.

Response

: P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage

: P405 - Store locked up.
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal

: P501 - Dispose of waste according to applicable legislation.

Hazardous ingredients

: propan-2-ol

Supplemental label elements

: Contains Fatty acids, C10-20-neo-. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Yes, applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Activator F Liquid

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
ethanol	EC: 200-578-6 CAS: 64-17-5	≥75 - ≤90	Flam. Liq. 2, H225 Eye Irrit. 2, H319	-	[1] [2]
Isopropyl alcohol	REACH #: 01-2119457558-25 EC: 200-661-7 CAS: 67-63-0 Index: 603-117-00-0	≥25 - ≤50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	-	[1] [2]
Fatty acids, C9-13-neo-, copper salts	REACH #: 01-2120796052-54 EC: 292-985-0 CAS: 91031-79-7	≥0.3 - <1	Acute Tox. 4, H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg M [Acute] = 1	[1] [2]
Fatty acids, C6-19-branched, copper (2+) salts	EC: 269-634-5 CAS: 68308-19-0	≥0.3 - <1	Acute Tox. 4, H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg M [Acute] = 1	[1] [2]
Fatty acids, C10-20-neo-	EC: 285-549-6 CAS: 85116-96-7	≥0.3 - <1	Skin Sens. 1B, H317 Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.	-	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

SECTION 4: First aid measures

- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Activator F Liquid

SECTION 5: Firefighting measures

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Activator F Liquid

SECTION 7: Handling and storage

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
ethanol	<p>DFG MAC-values list (Germany, 7/2024) Carc 5, Muta 5, Develop C. TWA 8 hours: 200 ppm. PEAK 15 minutes: 800 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 380 mg/m³. PEAK 15 minutes: 1520 mg/m³ 4 times per shift [Interval: 1 hour].</p> <p>TRGS 900 OEL (Germany, 3/2025) TWA 8 hours: 380 mg/m³. PEAK 15 minutes: 1520 mg/m³. TWA 8 hours: 200 ppm. PEAK 15 minutes: 800 ppm.</p>
Isopropyl alcohol	<p>DFG MAC-values list (Germany, 7/2024) Develop C. TWA 8 hours: 200 ppm. PEAK 15 minutes: 400 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 500 mg/m³. PEAK 15 minutes: 1000 mg/m³ 4 times per shift [Interval: 1 hour].</p> <p>TRGS 900 OEL (Germany, 3/2025) TWA 8 hours: 500 mg/m³. PEAK 15 minutes: 1000 mg/m³. TWA 8 hours: 200 ppm. PEAK 15 minutes: 400 ppm.</p>
Fatty acids, C9-13-neo-, copper salts	<p>DFG MAC-values list (Germany, 7/2024) [Copper and its inorganic compounds] Develop C. PEAK 15 minutes: 0.02 mg/m³ 4 times per shift [Interval: 1 hour]. Form: respirable fraction.</p>

Activator F Liquid

SECTION 8: Exposure controls/personal protection

Fatty acids, C6-19-branched, copper(2+) salts	<p>TWA 8 hours: 0.01 mg/m³. Form: respirable fraction. TRGS 900 OEL (Germany, 3/2025) [Kupfer und seine Verbindungen] PEAK 15 minutes: 0.8 mg/m³. Form: inhalable fraction. PEAK 15 minutes: 0.36 mg/m³. Form: alveolar fraction. TWA 8 hours: 0.2 mg/m³. Form: inhalable fraction. TWA 8 hours: 0.045 mg/m³. Form: alveolar fraction.</p> <p>DFG MAC-values list (Germany, 7/2024) [Copper and its inorganic compounds] Develop C. PEAK 15 minutes: 0.02 mg/m³ 4 times per shift [Interval: 1 hour]. Form: respirable fraction. TWA 8 hours: 0.01 mg/m³. Form: respirable fraction. TRGS 900 OEL (Germany, 3/2025) [Kupfer und seine Verbindungen] PEAK 15 minutes: 0.8 mg/m³. Form: inhalable fraction. PEAK 15 minutes: 0.36 mg/m³. Form: alveolar fraction. TWA 8 hours: 0.2 mg/m³. Form: inhalable fraction. TWA 8 hours: 0.045 mg/m³. Form: alveolar fraction.</p>
---	---

Biological exposure indices

Product/ingredient name	Exposure indices
Isopropyl alcohol	<p>DFG BEI-values list (Germany, 7/2024) BEI: 25 mg/l, acetone [in blood]. Sampling time: end of exposure or end of shift. BEI: 25 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift. TRGS 903 - BEI Values (Germany, 10/2024) BEI: 25 mg/l, acetone [in whole blood]. Sampling time: end of exposure or end of shift. BEI: 25 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift.</p>
Fatty acids, C9-13-neo-, copper salts	<p>DFG BEI-values list (Germany, 7/2024) [Copper and its inorganic compounds] BEI: See Section XV.2: For the following substances currently no BAR may be derived, but there is documentation in the "Occupational medicine and toxicology Justifications for BAT values, EKA, BLW, and BAR", copper [in urine]. Sampling time: Sample time not specified.</p>
Fatty acids, C6-19-branched, copper(2+) salts	<p>DFG BEI-values list (Germany, 7/2024) [Copper and its inorganic compounds] BEI: See Section XV.2: For the following substances currently no BAR may be derived, but there is documentation in the "Occupational medicine and toxicology Justifications for BAT values, EKA, BLW, and BAR", copper [in urine]. Sampling time: Sample time not specified.</p>

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

Result

Activator F Liquid

SECTION 8: Exposure controls/personal protection

ethanol

DNEL - General population - Long term - Oral
87 mg/kg bw/day
Effects: Systemic

DNEL - General population - Long term - Inhalation
114 mg/m³
Effects: Systemic

DNEL - General population - Long term - Dermal
206 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Long term - Dermal
343 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Long term - Inhalation
380 mg/m³
Effects: Systemic

DNEL - General population - Short term - Inhalation
950 mg/m³
Effects: Local

DNEL - Workers - Short term - Inhalation
1900 mg/m³
Effects: Local

Isopropyl alcohol

DNEL - General population - Long term - Oral
26 mg/kg bw/day
Effects: Systemic

DNEL - General population - Short term - Oral
51 mg/kg bw/day
Effects: Systemic

DNEL - General population - Long term - Inhalation
89 mg/m³
Effects: Systemic

DNEL - General population - Short term - Inhalation
178 mg/m³
Effects: Systemic

DNEL - General population - Long term - Dermal
319 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Long term - Inhalation
500 mg/m³
Effects: Systemic

DNEL - Workers - Long term - Dermal
888 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Short term - Inhalation
1000 mg/m³
Effects: Systemic

Fatty acids, C9-13-neo-, copper salts

DNEL - General population - Long term - Inhalation
0.39 mg/m³
Effects: Systemic

Activator F Liquid

SECTION 8: Exposure controls/personal protection

DNEL - General population - Long term - Oral

0.42 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

0.45 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.89 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

1.57 mg/m³

Effects: Systemic

Fatty acids, C10-20-neo-

DNEL - General population - Long term - Oral

17.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

17.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

25.79 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

29 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

86 mg/m³

Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

SECTION 8: Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): Protective gloves made of nitrile rubber (material thickness of 0,4 mm); EN 374-5 Cat. III ; 4 - 8 hours (breakthrough time): Protective gloves made of Viton®/ butyl rubber (material thickness of 0,7 mm); EN388 Cat.II / EN374 Cat.III / EN374-2
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Green.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- Melting point/freezing point** : Not available.
- Boiling point or initial boiling point and boiling range** : >78°C (>172.4°F)
- Flammability** : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts. Emits toxic fumes when heated to decomposition.
- Lower and upper explosion limit** : Not available.
- Flash point** : Closed cup: <23°C (<73.4°F)
- Auto-ignition temperature** : Not applicable.
- Decomposition temperature** : Not available.
- pH** : Not applicable.
- Viscosity** : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): Not available.
- Solubility** :
Not available.

Activator F Liquid

SECTION 9: Physical and chemical properties

Solubility in water : Not available.

Partition coefficient n-octanol/ water (log Pow) : Not applicable.

Vapor pressure :

Ingredient name	Vapor Pressure at 20 °C			Vapor pressure at 50 °C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
ethanol	42.94865	5.7				
Isopropyl alcohol	33.00268	4.4				
Fatty acids, C10-20-neo-	0.000067	0.0000089	EU A.4			

Relative density : Not available.

Density : 0.8 g/cm³

Relative vapor density : Not available.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Explosive in the presence of the following materials or conditions: oxidizing materials and reducing materials.

Oxidizing properties : Not available.

9.2.2 Other safety characteristics

Miscible with water : No.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials : Reactive or incompatible with the following materials: oxidizing materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Highly reactive or incompatible with the following materials: oxidizing materials, reducing materials, acids and alkalis.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result
-------------------------	--------

Activator F Liquid

SECTION 11: Toxicological information

ethanol	Rat - Oral - LD50 7 g/kg
	Rat - Inhalation - LC50 Vapor 124700 mg/m ³ [4 hours]
Isopropyl alcohol	Rabbit - Dermal - LD50 12800 mg/kg
	Rat - Oral - LD50 5000 mg/kg <u>Toxic effects:</u> Behavioral - General anesthetic

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
ethanol	7000	N/A	N/A	124.7	N/A
Isopropyl alcohol	5000	12800	N/A	N/A	N/A
Fatty acids, C9-13-neo-, copper salts	500	N/A	N/A	N/A	N/A
Fatty acids, C6-19-branched, copper(2+) salts	500	N/A	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name

ethanol

Result

Rabbit - Skin - Mild irritant

Amount/concentration applied: 400 mg

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

Isopropyl alcohol

Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

ethanol

Result

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 0.066666667 minutes

Amount/concentration applied: 100 mg

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 uL

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 500 mg

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 1 hours

Amount/concentration applied: 50 pph

Activator F Liquid

SECTION 11: Toxicological information

Isopropyl alcohol

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 10 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

Isopropyl alcohol

Result

STOT SE 3, H336 (Narcotic effects)

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Activator F Liquid

SECTION 11: Toxicological information

Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary [Product]** : Not available.
- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

- Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

Activator F Liquid

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

ethanol

Result

Acute - LC50 - Fresh water

Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*
42 mg/l [4 days]
Effect: Mortality

Acute - EC50 - Marine water

Algae - Green algae - *Ulva pertusa*
17.921 mg/l [96 hours]
Effect: Reproduction

Chronic - NOEC - Marine water

Algae - Green algae - *Ulva pertusa*
4.995 mg/l [96 hours]
Effect: Reproduction

Chronic - NOEC - Fresh water

Fish - Eastern mosquitofish - *Gambusia holbrooki* - Larvae
Age: 3 days
0.375 µl/l [12 weeks]
Effect: Morphology

Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna* - Neonate
Age: <24 hours
100 µl/l [21 days]
Effect: Mortality

Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*
2 mg/l [48 hours]
Effect: Intoxication

Isopropyl alcohol

Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - *Crangon crangon*
1400 mg/l [48 hours]
Effect: Mortality

Acute - LC50 - Fresh water

Fish - Harlequinfish, red rasbora - *Rasbora heteromorpha*
Size: 1 to 3 cm
4200 mg/l [96 hours]
Effect: Mortality

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
ethanol	-0.35	-	Low
Isopropyl alcohol	0.05	-	Low
Fatty acids, C10-20-neo-	>3	-	Low

Activator F Liquid

SECTION 12: Ecological information

12.4 Mobility in soil

Soil/Water partition coefficient

Product/ingredient name	logKoc	Koc
ethanol	0.2	1.59008
Isopropyl alcohol	0.54	3.4364

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
ethanol	No	No	No	No	No	No	No
Isopropyl alcohol	No	No	No	No	No	No	No
Fatty acids, C9-13-neo-, copper salts	No	No	No	No	No	No	No
Fatty acids, C6-19-branched, copper(2+) salts	No	No	No	No	No	No	No
Fatty acids, C10-20-neo-	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
ethanol	No	N/A	N/A	No	N/A	N/A	N/A
Isopropyl alcohol	No	N/A	N/A	No	N/A	N/A	N/A
Fatty acids, C9-13-neo-, copper salts	No	N/A	N/A	No	N/A	N/A	N/A
Fatty acids, C6-19-branched, copper(2+) salts	No	N/A	N/A	No	N/A	N/A	N/A
Fatty acids, C10-20-neo-	No	N/A	N/A	No	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
ethanol	No	No	No	No	No	No	No
Isopropyl alcohol	No	No	No	No	No	No	No
Fatty acids, C9-13-neo-, copper salts	No	No	No	No	No	No	No
Fatty acids, C6-19-branched, copper(2+) salts	No	No	No	No	No	No	No
Fatty acids, C10-20-neo-	No	No	No	No	No	No	No

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.

Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

Activator F Liquid

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Can	15 01 10* packaging containing residues of or contaminated by hazardous substances

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1987	UN1987	UN1987	UN1987
14.2 UN proper shipping name	ALCOHOLS, N.O.S. (ethanol, Isopropyl alcohol)	ALCOHOLS, N.O.S. (ethanol, Isopropyl alcohol)	ALCOHOLS, N.O.S. (ethanol, Isopropyl alcohol)	Alcohols, n.o.s. (ethanol, Isopropyl alcohol)
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

Activator F Liquid

SECTION 14: Transport information

- ADR/RID** : **Hazard identification number** 33
Limited quantity 1 L
Special provisions 601, 274, 640D
Tunnel code (D/E)
ADR Classification Code: F1
- ADN** : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.
Special provisions 274, 601, 640D
- IMDG** : **Emergency schedules** F-E, S-D
Special provisions 274
- IATA** : **Quantity limitation** Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353. Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y341.
Special provisions A3, A180
- 14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed above the relevant limit.

Substances of very high concern

None of the components are listed above the relevant limit.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
Activator F Liquid	≥90	3

Labeling : Not applicable.

Synthetic polymer microparticles - Designation 78

Generic identity of polymer(s) : Not applicable.

Total percentage of synthetic polymer microparticles : Not applicable.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Activator F Liquid

SECTION 15: Regulatory information

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

P5c

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
ethanol	DFG MAC-values list	-	Carc 5, Muta 5, Develop C	-
propan-2-ol	DFG MAC-values list	-	Develop C	-
Fatty acids, C9-13-neo-, copper salts	DFG MAC-values list	Copper and its inorganic compounds	Develop C	-
Fatty acids, C6-19-branched, copper(2+) salts	DFG MAC-values list	Copper and its inorganic compounds	Develop C	-

Storage class (TRGS 510) : 3

Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

Danger criteria

Category	Reference number
P5c	1.2.5.3

Hazard class for water : 2

Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
5.2.2 [III]	Dusty inorganic substances	1.1
5.2.5	Organic substances	125.6
5.2.5 [I]	Organic substances	125

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : Not determined.

Activator F Liquid

SECTION 15: Regulatory information

Canada	: Not determined.
China	: All components are listed or exempted.
Eurasian Economic Union	: Russian Federation inventory : All components are listed or exempted.
Japan	: Japan inventory (CSCL) : Not determined. Japan inventory (ISHL) : Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: All components are listed or exempted.

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate B = Bioaccumulative BCF = Bioconcentration Factor CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods IMO = International Maritime Organization M = Mobile N/A = Not available P = Persistent PBT = Persistent, Bioaccumulative and Toxic PMT = Persistent, Mobile and Toxic PNEC = Predicted No Effect Concentration RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SGG = Segregation Group T = Toxic vB = Very Bioaccumulative vM = Very Mobile vP = Very Persistent vPvB = Very Persistent and Very Bioaccumulative vPvM = Very Persistent and Very Mobile
-----------------------------------	--

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	On basis of test data Calculation method Calculation method

Full text of abbreviated H statements

Activator F Liquid

SECTION 16: Other information

H225	Highly flammable liquid and vapor.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Date of printing : 05/02/2026

Date of issue/ Date of revision : 29/01/2026

Date of previous issue : 04/11/2025

Version : 4.4

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.