

SAFETY DATA SHEET



Anti-Seize Assembly Paste Presspack

Section 1. Identification

Product identifier : Anti-Seize Assembly Paste Presspack
Product code : 260001
Other means of identification : Not available.
Product type : Aerosol.
Color : Gray.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Aerosol product
Corrosion inhibitor.Lubricating agent
When using Anti-Seize on chrome-nickel steel, the formation of chromium(VI) can occur above 400°C.

Uses advised against

Not applicable.

Supplier's details : WEICON GmbH & Co. KG
Königsberger Str. 255,
48157 Münster, Germany
phone:+49 251 93220,
email: info@weicon.de,
URL: www.weicon.de

e-mail address of person responsible for this SDS : msds@weicon.de

National contact

WEICON Canada Inc.
20 Steckle Place, Unit 20
Kitchener, Ontario N2E 2C3, CA
www.weicon.ca
E-mail: info@weicon.ca
Telephone: +1-519-896-5252
Telefax: +1-519-896-5254

Emergency telephone number (with hours of operation) : +1 866 928 0789 (24h - Toll free)
TRANSPORT EMERGENCY CONTACT :+1 866 928 0789 ((24h - Toll free)

Section 2. Hazard identification

Classification of the substance or mixture : AEROSOLS - Category 3
SERIOUS EYE DAMAGE - Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H229 - Pressurized container: may burst if heated.
H318 - Causes serious eye damage.

Precautionary statements

Section 2. Hazard identification

- Prevention** : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 - Do not pierce or burn, even after use.
P280 - Wear eye or face protection.
- Response** : P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
- Storage** : P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- Disposal** : Not applicable.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

| Ingredient name | Synonyms | % (v/v) | Identifiers |
|--|---|-----------|--------------------|
| Distillates (petroleum), hydrotreated light naphthenic | Baseoil - unspecified; Distillates, petroleum, hydrotreated light naphthenic; Hydrotreated light naphthenic distillate, solvent extract, petroleum; Mineral oil, petroleum distillates, hydrotreated light naphthenic; Mineral oil, petroleum distillates, hydrotreated (severe) light naphthenic; Hydrotreated light naphthenic distillate (petroleum); Distillates (petroleum), hydro-treated light naphthenic; Hydrotreated light naphthenic distillate solvent extract (petroleum); Hydrotreated light naphthenic distillate; Hydrotreated light naphthenic (petroleum) | ≥10 - ≤30 | CAS: 64742-53-6 |
| calcium dihydroxide | Calcium hydroxide; Slaked lime; Hydrated lime; Caustic lime; Calcium hydrate; calcium hydroxide (Ca(OH) 2); MILK OF LIME; Calcium hydroxyde | ≥5 - ≤10 | CAS: 1305-62-0 |
| copper | copper flakes; Copper, powder; Copper Fume (as Cu); Copper Dust and mists (as Cu); COPPER DUSTS AND MISTS; Copper metal fumes; Copper metal dusts; Copper, fume; Copper , dusts & mists; Copper concentrate; Copper metal | ≥1 - ≤5 | CAS: 7440-50-8 |

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

Section 4. First-aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
halogenated compounds
metal oxide/oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Section 6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|--|--|
| Distillates (petroleum), hydrotreated light naphthenic | <p>CA Ontario Provincial (Canada, 6/2019) [Mineral oil, excluding metal working fluids (pure, highly and severely refined)] TWA 8 hours: 5 mg/m³. Form: inhalable particulate matter.</p> <p>CA Alberta Provincial (Canada, 3/2023) [Oil] OEL 8 hours: 5 mg/m³. Form: mist. OEL 15 minutes: 10 mg/m³. Form: mist.</p> <p>CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 10 mg/m³. TWA 8 hours: 5 mg/m³.</p> <p>CA British Columbia Provincial (Canada, 3/2025) TWA 8 hours: 5 mg/m³.</p> <p>CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 5 mg/m³.</p> |
| calcium dihydroxide | |

Section 8. Exposure controls/personal protection

copper

CA Quebec Provincial (Canada, 2/2024)
 TWAEV 8 hours: 5 mg/m³.

CA Alberta Provincial (Canada, 3/2023)
 OEL 8 hours: 5 mg/m³.

CA Saskatchewan Provincial (Canada, 4/2021)
 STEL 15 minutes: 3 mg/m³ (measured as Cu). Form: dust and mist.
 STEL 15 minutes: 0.6 mg/m³ (measured as Cu). Form: Fume.
 TWA 8 hours: 1 mg/m³ (measured as Cu). Form: dust and mist.
 TWA 8 hours: 0.2 mg/m³ (measured as Cu). Form: Fume.

CA British Columbia Provincial (Canada, 3/2025) [copper (fume)]
 TWA 8 hours: 0.2 mg/m³ (as Cu). Form: fume.

CA British Columbia Provincial (Canada, 3/2025) [copper (dusts and mists)]
 TWA 8 hours: 1 mg/m³ (as Cu). Form: dusts and mists.

CA Ontario Provincial (Canada, 6/2019)
 TWA 8 hours: 1 mg/m³ (as Cu). Form: dust and mists.
 TWA 8 hours: 0.2 mg/m³ (as Cu). Form: fume.

CA Quebec Provincial (Canada, 2/2024) [Copper, fume]
 TWAEV 8 hours: 0.2 mg/m³ (as Cu). Form: fume.

CA Quebec Provincial (Canada, 2/2024) [Copper , dusts & mists]
 TWAEV 8 hours: 1 mg/m³ (as Cu). Form: dusts & mists.

CA Alberta Provincial (Canada, 3/2023) [Copper (fume)]
 OEL 8 hours: 0.2 mg/m³. Form: fume.

CA Alberta Provincial (Canada, 3/2023) [Copper (dust/mists)]
 OEL 8 hours: 1 mg/m³ (as Cu). Form: dusts and mists.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Section 8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): Protective gloves made of nitrile rubber (material thickness of 0,4 mm); EN 374-5 Cat. III 4 - 8 hours (breakthrough time): Protective gloves made of Viton®/ butyl rubber (material thickness of 0,7 mm); EN388 Cat.II / EN374 Cat.III / EN374-2
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Gas.
- Color** : Gray.
- Odor** : Benzene-like.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point/freezing point** : Not applicable.
- Boiling point or initial boiling point and boiling range** : Not available.
- Flash point** : Closed cup: >93.3°C (>199.9°F) [Product does not sustain combustion.]
- Evaporation rate** : Not available.
- Flammability** : Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.
Slightly flammable in the presence of the following materials or conditions: heat.
- Lower and upper explosion limit/flammability limit** : Not available.
- Vapor pressure** : Not available.
- Relative vapor density** : Not available.

Section 9. Physical and chemical properties

| | |
|---|---|
| Relative density | : Not applicable. |
| Density | : 1.2 g/cm ³ [20°C (68°F)] |
| Solubility in water | : Not available. |
| Miscible with water | : No. |
| Partition coefficient: n-octanol/water | : Not applicable. |
| Auto-ignition temperature | : Not applicable. |
| Decomposition temperature | : Not available. |
| Viscosity | : Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): Not applicable. |

Particle characteristics

Median particle size : Not applicable.

Aerosol product

Type of aerosol : Spray

Section 10. Stability and reactivity

| | |
|---|--|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

Distillates (petroleum), hydrotreated light naphthenic

Result

Rat - Oral - LD50

>5000 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity)

Rat - Inhalation - LC50 Dusts and mists

2180 mg/m³ [4 hours]

Toxic effects: Lung, Thorax, or Respiration - Structural or functional change in trachea or bronchi

calcium dihydroxide

Rat - Oral - LD50

7340 mg/kg

Conclusion/Summary [Product] : Not available.

Skin corrosion/irritation

Product/ingredient name

Result

Section 11. Toxicological information

Distillates (petroleum), hydrotreated light naphthenic

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 0.5 MI

Rabbit - Skin - Severe irritant

Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

calcium dihydroxide

Result

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 10 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Classification

| Product/ingredient name | IARC | NTP | ACGIH |
|--|------|-----|-------|
| Distillates (petroleum), hydrotreated light naphthenic | - | - | A4 |

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Section 11. Toxicological information

Product/ingredient name

calcium dihydroxide

Result

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name

Distillates (petroleum), hydrotreated light naphthenic

Result

ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Not available.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : No known significant effects or critical hazards.

Section 11. Toxicological information

- Carcinogenicity** : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------------------|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| Anti-Seize Assembly Paste Presspack | 13333.3 | N/A | N/A | N/A | N/A |
| calcium dihydroxide | 7340 | N/A | N/A | N/A | N/A |
| copper | 500 | N/A | N/A | N/A | N/A |

Section 12. Ecological information

Toxicity

Product/ingredient name

calcium dihydroxide

Result

Acute - LC50 - Fresh water

Fish - Zambezi barbel - *Clarias gariepinus* - Fingerling
 33.8844 mg/l [96 hours]

Effect: Mortality

copper

Acute - LC50 - Marine water

Crustaceans - Scud Order - *Amphipoda* - Adult

Size: 9 mm

0.072 µg/l [48 hours]

Effect: Mortality

Chronic - NOEC - Marine water

Algae - Diatom - *Nitzschia closterium* - Exponential growth phase

2.5 µg/l [72 hours]

Effect: Population

Chronic - NOEC - Fresh water

Fish - Nile tilapia - *Oreochromis niloticus* - Juvenile (Fledgling, Hatchling, Weanling)

Weight: 8.3 g

0.8 µg/l [6 weeks]

Effect: Biochemistry

Acute - LC50 - Marine water

Fish - Mudskipper - *Periophthalmus waltoni* - Adult

7.56 µg/l [96 hours]

Effect: Mortality

Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*

2 µg/l [21 days]

Effect: Mortality

Acute - IC50 - Fresh water

Algae - Green algae - *Raphidocelis subcapitata* - Exponential growth phase

13 µg/l [72 hours]

Effect: Population

Conclusion/Summary [Product] : Not available.

Section 12. Ecological information

Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/Water partition coefficient : Not available.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

| | TDG Classification | DOT Classification | IMDG | IATA |
|-----------------------------------|--|--|---|--|
| UN number | UN1950 | UN1950 | UN1950 | UN1950 |
| UN proper shipping name | AEROSOLS | Aerosols | AEROSOLS (1,3,3,3-Tetrafluoropropylene) | Aerosols, non-flammable (1,3,3,3-Tetrafluoropropylene) |
| Transport hazard class(es) | 2.2   | 2.2   | 2.2   | 2.2  |
| Packing group | - | - | - | - |
| Environmental hazards | Yes. | Yes. | Yes. | Yes. The environmentally hazardous substance mark is not required. |

Additional information

TDG Classification : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail.
Explosive Limit and Limited Quantity Index 1
Passenger Carrying Road or Rail Index 75
Special provisions 80, 107

Section 14. Transport information

- DOT Classification** : This product is not regulated as a marine pollutant when transported on inland waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.
Limited quantity Yes.
Packaging instruction Exceptions: 306. Non-bulk: None. Bulk: None.
Quantity limitation Passenger aircraft/rail: 75 kg. Cargo aircraft: 150 kg.
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Emergency schedules F-D, S-U
Special provisions 63, 190, 277, 327, 344, 381, 959
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.
Quantity limitation Passenger and Cargo Aircraft: 75 kg. Packaging instructions: 203. Cargo Aircraft Only: 150 kg. Packaging instructions: 203. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y203.
Special provisions A98, A145, A167, A802
- Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

Canadian lists

- Canadian NPRI** : The following components are listed: aluminum (fume or dust only); copper (and its compounds); zinc (and its compounds); zinc (and its compounds)
- CEPA Toxic substances** : None of the components are listed.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

- Australia** : Not determined.
- Canada** : Not determined.
- China** : Not determined.
- Eurasian Economic Union** : **Russian Federation inventory:** All components are listed or exempted.
- Japan** : **Japan inventory (CSCL):** Not determined.
Japan inventory (ISHL): Not determined.
- New Zealand** : Not determined.
- Philippines** : Not determined.
- Republic of Korea** : Not determined.
- Taiwan** : All components are listed or exempted.

Section 15. Regulatory information

| | |
|----------------------|--|
| Thailand | : Not determined. |
| Turkey | : Not determined. |
| United States | : Not determined. |
| Viet Nam | : All components are listed or exempted. |

Section 16. Other information

History

| | |
|---------------------------------------|-------------|
| Date of printing | : 2/2/2026 |
| Date of issue/Date of revision | : 1/29/2026 |
| Date of previous issue | : 11/4/2025 |
| Version | : 3.1 |

Key to abbreviations

| |
|---|
| : ATE = Acute Toxicity Estimate |
| : BCF = Bioconcentration Factor |
| : DOT = Department of Transportation |
| : GHS = Globally Harmonized System of Classification and Labelling of Chemicals |
| : HPR = Hazardous Products Regulations |
| : IATA = International Air Transport Association |
| : IBC = Intermediate Bulk Container |
| : IMDG = International Maritime Dangerous Goods |
| : IMO = International Maritime Organization |
| : LogPow = logarithm of the octanol/water partition coefficient |
| : MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) |
| : N/A = Not available |
| : SGG = Segregation Group |
| : TDG = Transportation of Dangerous Goods |
| : UN = United Nations |

Procedure used to derive the classification

| Classification | Justification |
|--|---|
| AEROSOLS - Category 3 SERIOUS EYE DAMAGE - Category 1 | On basis of test data Calculation method |

References : Not available.

✔ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.