

# SAFETY DATA SHEET

## Rust Loosener and Contact Spray

### Section 1. Identification

|                                      |                                   |
|--------------------------------------|-----------------------------------|
| <b>GHS product identifier</b>        | : Rust Loosener and Contact Spray |
| <b>Product code</b>                  | : 111500                          |
| <b>Other means of identification</b> | : Not available.                  |
| <b>Color</b>                         | : Colorless.                      |
| <b>Product type</b>                  | : Aerosol.                        |

#### Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Aerosol product

##### Uses advised against

Not applicable.

|                           |  |
|---------------------------|--|
| <b>Supplier's details</b> | : WEICON GmbH & Co. KG<br>Königsberger Str. 255,<br>48157 Münster, Germany<br>phone:+49 251 93220,<br>email: info@weicon.de,<br>URL: www.weicon.de |
|---------------------------|--|

|  |                  |
|--|------------------|
| <b>e-mail address of person responsible for this SDS</b> | : msds@weicon.de |
|--|------------------|

|   |  |
|---|--|
| <b>Emergency telephone number (with hours of operation)</b> | : +1 202 464 2554<br>TRANSPORT (24 Hours/Day): +1 202 464 2554 |
|---|--|

### Section 2. Hazards identification

|                        |   |
|------------------------|---|
| <b>OSHA/HCS status</b> | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). |
|------------------------|---|

|   |                         |
|---|-------------------------|
| <b>Classification of the substance or mixture</b> | : AEROSOLS - Category 1 |
|---|-------------------------|

#### GHS label elements

##### Hazard pictograms



|                    |          |
|--------------------|----------|
| <b>Signal word</b> | : Danger |
|--------------------|----------|

|                          |   |
|--------------------------|---|
| <b>Hazard statements</b> | : H222, H229 - Extremely flammable aerosol. Pressurized container: may burst if heated. |
|--------------------------|---|

#### Precautionary statements

|                   |  |
|-------------------|--|
| <b>Prevention</b> | : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P211 - Do not spray on an open flame or other ignition source.<br>P251 - Do not pierce or burn, even after use. |
|-------------------|--|

|                 |                   |
|-----------------|-------------------|
| <b>Response</b> | : Not applicable. |
|-----------------|-------------------|

|                |  |
|----------------|--|
| <b>Storage</b> | : P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F/50 °C. |
|----------------|--|

|                 |                   |
|-----------------|-------------------|
| <b>Disposal</b> | : Not applicable. |
|-----------------|-------------------|

## Section 2. Hazards identification

- Hazards not otherwise classified** : None known.
- Hazards identified when used** : No known significant effects or critical hazards.

## Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

| Ingredient name  | Synonyms  | %         | Identifiers   |
|--|---|-----------|---------------|
| Hydrocarbons, C10-13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics |   | ≥10 - ≤30 | -             |
| propane  | Propyl hydride; n-Propane; Dimethyl methane; E 944; HC-290; R290; PROPYL HYDRID; Normal propane; liquefied petroleum gas; Propagas; n-propana | ≥3 - ≤7   | CAS: 74-98-6  |
| Butane (containing ≥ 0.1% butadiene (203-450-8))                         |   | ≥1 - ≤5   | CAS: 106-97-8 |
| Isobutane (Containing ≥ 0.1% butadiene (203-450-8))                      |   | ≥0.1 - ≤1 | CAS: 75-28-5  |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
irritation  
redness

## Section 4. First aid measures

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

**Specific hazards arising from the chemical** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

## Section 6. Accidental release measures

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name   | Exposure limits  |
|---|--|
| Hydrocarbons, C10-13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics<br>propane | None.<br><br><b>NIOSH REL (United States, 10/2020)</b><br>TWA 10 hours: 1000 ppm.<br>TWA 10 hours: 1800 mg/m <sup>3</sup> .<br><b>CAL OSHA PEL (United States, 1/2025)</b><br>TWA 8 hours: 1800 mg/m <sup>3</sup> .<br>TWA 8 hours: 1000 ppm.<br><b>OSHA PEL (United States, 5/2018)</b><br>TWA 8 hours: 1000 ppm.<br>TWA 8 hours: 1800 mg/m <sup>3</sup> .<br><b>OSHA PEL 1989 (United States, 3/1989)</b><br>TWA 8 hours: 1000 ppm.<br>TWA 8 hours: 1800 mg/m <sup>3</sup> . |
| Butane (containing >= 0.1% butadiene (203-450-8))                                   | <b>ACGIH TLV (United States, 1/2025)</b> Oxygen depletion [asphyxiant] , Explosive potential.<br><b>NIOSH REL (United States, 10/2020)</b><br>TWA 10 hours: 800 ppm.<br>TWA 10 hours: 1900 mg/m <sup>3</sup> .   |

## Section 8. Exposure controls/personal protection

Isobutane (Containing  $\geq$  0.1% butadiene (203-450-8))

**CAL OSHA PEL (United States, 1/2025)**

TWA 8 hours: 1900 mg/m<sup>3</sup>.

TWA 8 hours: 800 ppm.

**OSHA PEL 1989 (United States, 3/1989)**

TWA 8 hours: 800 ppm.

TWA 8 hours: 1900 mg/m<sup>3</sup>.

**ACGIH TLV (United States, 1/2025) [Butane]**

Explosive potential.

STEL 15 minutes: 1000 ppm.

**NIOSH REL (United States, 10/2020)**

TWA 10 hours: 800 ppm.

TWA 10 hours: 1900 mg/m<sup>3</sup>.

**ACGIH TLV (United States, 1/2025) [Butane]**

Explosive potential.

STEL 15 minutes: 1000 ppm.

### Biological exposure indices

No exposure indices known.

### Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### Skin protection

##### Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): Protective gloves made of nitrile rubber (material thickness of 0,4 mm); EN 374-5 Cat. III 4 - 8 hours (breakthrough time): Protective gloves made of Viton®/ butyl rubber (material thickness of 0,7 mm); EN388 Cat.II / EN374 Cat.III / EN374-2

##### Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

##### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Section 8. Exposure controls/personal protection

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

|   |   |
|---|---|
| <b>Physical state</b>   | : Gas.  |
| <b>Color</b>  | : Colorless.  |
| <b>Odor</b>   | : Characteristic.   |
| <b>Odor threshold</b>   | : Not available.  |
| <b>pH</b>   | : Not applicable.   |
| <b>Melting point/freezing point</b>                             | : Not applicable.   |
| <b>Boiling point or initial boiling point and boiling range</b> | : -44.5°C (-48.1°F)   |
| <b>Flash point</b>  | : Closed cup: -97°C (-142.6°F)  |
| <b>Fire point</b>   | : 236°C (456.8°F)   |
| <b>Evaporation rate</b>   | : Not available.  |
| <b>Flammability</b>   | : Extremely flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.<br>Highly flammable in the presence of the following materials or conditions: heat. |
| <b>Lower and upper explosion limit/flammability limit</b>       | : Lower: 0.7%<br>Upper: 10.9%   |
| <b>Vapor pressure</b>   | : 830 kPa (6225.5 mm Hg)  |
| <b>Relative vapor density</b>                                   | : Not available.  |
| <b>Relative density</b>   | : Not applicable.   |
| <b>Density</b>  | : 0.803 g/cm <sup>3</sup> [20°C (68°F)]   |
| <b>Solubility in water</b>                                      | : Not available.  |
| <b>Miscible with water</b>                                      | : No.   |
| <b>Partition coefficient: n-octanol/water</b>                   | : Not applicable.   |
| <b>Auto-ignition temperature</b>                                | : Not applicable.   |
| <b>Decomposition temperature</b>                                | : Not available.  |
| <b>Heat of combustion</b>                                       | : 3.919 kJ/g  |
| <b>Viscosity</b>  | : Dynamic (room temperature): Not available.<br>Kinematic (room temperature): Not available.<br>Kinematic (40°C (104°F)): Not available.  |

### Particle characteristics

**Median particle size** : Not applicable.

### Aerosol product

**Type of aerosol** : Spray

## Section 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

**Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

## Section 10. Stability and reactivity

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).

**Incompatible materials** : No specific data.

**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name                              | Result   |
|--|--|
| Butane (containing >= 0.1% butadiene (203-450-8))    | <b>Rat - Inhalation - LC50 Vapor</b><br>658000 mg/m <sup>3</sup> [4 hours] |
| Isobutane (Containing >= 0.1% butadiene (203-450-8)) | <b>Rat - Inhalation - LC50 Vapor</b><br>658000 mg/m <sup>3</sup> [4 hours] |

**Conclusion/Summary [Product]** : Not available.

#### Skin corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

#### Serious eye damage/eye irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

#### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

#### Respiratory or skin sensitization

Not available.

#### Skin

**Conclusion/Summary [Product]** : Not available.

#### Respiratory

**Conclusion/Summary [Product]** : Not available.

#### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

#### Carcinogenicity

## Section 11. Toxicological information

Not available.

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

#### **Product/ingredient name**

Hydrocarbons, C10-13, n-alkanes,  
isoalkanes, cycloalkanes, <2% aromatics

#### **Result**

ASPIRATION HAZARD - Category 1

### Information on the likely routes of exposure

Not available.

### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
  - irritation
  - redness
- Inhalation** : Adverse symptoms may include the following:
  - respiratory tract irritation
  - coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### **Long term exposure**

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

## Section 11. Toxicological information

Not available.

**Conclusion/Summary [Product]** : Not available.

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

| Product/ingredient name                                   | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| Butane (containing $\geq 0.1\%$ butadiene (203-450-8))    | N/A          | N/A            | N/A                      | 658                        | N/A                                 |
| Isobutane (Containing $\geq 0.1\%$ butadiene (203-450-8)) | N/A          | N/A            | N/A                      | 658                        | N/A                                 |

## Section 12. Ecological information

### Toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Persistence and degradability

Not available.

**Conclusion/Summary [Product]** : Not available.

### Bioaccumulative potential

| Product/ingredient name                                   | LogP <sub>ow</sub> | BCF | Potential |
|---|--------------------|-----|-----------|
| propane   | 1.09               | -   | Low       |
| Isobutane (Containing $\geq 0.1\%$ butadiene (203-450-8)) | 2.8                | -   | Low       |

### Mobility in soil

**Soil/Water partition coefficient** : Not available.

### Other adverse effects

No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## Section 14. Transport information

|                            | DOT<br>Classification  | TDG<br>Classification  | Mexico<br>Classification   | IMDG   | IATA   |
|----------------------------|--|--|--|--|--|
| UN number                  | UN1950   | UN1950   | UN1950   | UN1950   | UN1950   |
| UN proper shipping name    | Aerosols   | AEROSOLS   | AEROSOLS   | AEROSOLS   | Aerosols, flammable  |
| Transport hazard class(es) | 2.1<br> | 2.1<br> | 2.1<br> | 2.1<br> | 2.1<br> |
| Packing group              | -  | -  | -  | -  | -  |
| Environmental hazards      | No.  | No.  | No.  | No.  | No.  |

### Additional information

#### DOT Classification

: **Limited quantity** Yes.  
**Packaging instruction** Exceptions: 306. Non-bulk: None. Bulk: None.  
**Quantity limitation** Passenger aircraft/rail: 75 kg. Cargo aircraft: 150 kg.  
**Special provisions** N82

#### TDG Classification

: Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).  
**Explosive Limit and Limited Quantity Index** 1  
**Passenger Carrying Road or Rail Index** 75  
**Special provisions** 80, 107

#### Mexico Classification

: **Special provisions** 63, 190, 277, 327, 344

#### IMDG

: **Emergency schedules** F-D, S-U  
**Special provisions** 63, 190, 277, 327, 344, 381, 959

#### IATA

: **Quantity limitation** Passenger and Cargo Aircraft: 75 kg. Packaging instructions: 203. Cargo Aircraft Only: 150 kg. Packaging instructions: 203. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y203.  
**Special provisions** A145, A167, A802

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

## Section 15. Regulatory information

### U.S. Federal regulations

**TSCA 8(a) CDR Exempt/Partial exemption:** Not determined

**Clean Air Act (CAA) 112 regulated flammable substances:** propane; Butane (containing  $\geq 0.1\%$  butadiene (203-450-8))

### TSCA 12(b) - Chemical export notification

Not applicable.

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Not listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : AEROSOLS - Category 1

#### Composition/information on ingredients

| Name   | %                   | Classification   |
|--|---------------------|--|
| Hydrocarbons, C10-13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics | $\geq 10 - \leq 30$ | ASPIRATION HAZARD - Category 1   |
| propane  | $\geq 3 - \leq 7$   | FLAMMABLE GASES - Category 1A<br>GASES UNDER PRESSURE - Compressed gas |
| Butane (containing $\geq 0.1\%$ butadiene (203-450-8))                   | $\geq 1 - \leq 5$   | FLAMMABLE GASES - Category 1A<br>GASES UNDER PRESSURE - Compressed gas |
| Isobutane (Containing $\geq 0.1\%$ butadiene (203-450-8))                | $\geq 0.1 - \leq 1$ | FLAMMABLE GASES - Category 1A<br>GASES UNDER PRESSURE - Compressed gas |

### State regulations

**Massachusetts** : The following components are listed: PROPANE; BUTANE

**New York** : None of the components are listed.

**New Jersey** : The following components are listed: PROPANE; BUTANE

**Pennsylvania** : The following components are listed: PROPANE; BUTANE

### California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

## Section 15. Regulatory information

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

|                                |   |
|--------------------------------|---|
| <b>Australia</b>               | : All components are listed or exempted.  |
| <b>Canada</b>                  | : Not determined.   |
| <b>China</b>                   | : All components are listed or exempted.  |
| <b>Eurasian Economic Union</b> | : <b>Russian Federation inventory</b> : Not determined.   |
| <b>Japan</b>                   | : <b>Japan inventory (CSCL)</b> : All components are listed or exempted.<br><b>Japan inventory (ISHL)</b> : Not determined. |
| <b>New Zealand</b>             | : Not determined.   |
| <b>Philippines</b>             | : Not determined.   |
| <b>Republic of Korea</b>       | : Not determined.   |
| <b>Taiwan</b>                  | : Not determined.   |
| <b>Thailand</b>                | : Not determined.   |
| <b>Turkey</b>                  | : Not determined.   |
| <b>United States</b>           | : All components are active or exempted.  |
| <b>Viet Nam</b>                | : Not determined.   |

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

|                  |   |   |
|------------------|---|---|
| Health           | / | 0 |
| Flammability     |   | 4 |
| Physical hazards |   | 0 |
|                  |   |   |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### National Fire Protection Association (U.S.A.)



### Procedure used to derive the classification

| Classification        | Justification         |
|-----------------------|-----------------------|
| AEROSOLS - Category 1 | On basis of test data |

### History

|                                       |             |
|---------------------------------------|-------------|
| <b>Date of printing</b>               | : 2/3/2026  |
| <b>Date of issue/Date of revision</b> | : ***       |
| <b>Date of previous issue</b>         | : 11/4/2025 |
| <b>Version</b>                        | : 2.1       |

## Section 16. Other information

### Key to abbreviations

: ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
DOT = Department of Transportation  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
IMO = International Maritime Organization  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
TDG = Transportation of Dangerous Goods  
UN = United Nations

### References

: Not available.

✔ Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.