

# SAFETY DATA SHEET



## WEICON Anti-Static Epoxy Hardener

### Section 1. Identification

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| <b>GHS product identifier</b>        | : WEICON Anti-Static Epoxy Hardener |
| <b>Product code</b>                  | : 171002                            |
| <b>Other means of identification</b> | : Not available.                    |
| <b>Color</b>                         | : Yellow. [Dark]                    |
| <b>Product type</b>                  | : Liquid.                           |

#### Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Hardener for resins.

##### Uses advised against

Not applicable.

|                           |  |
|---------------------------|--|
| <b>Supplier's details</b> | : WEICON GmbH & Co. KG<br>Königsberger Str. 255,<br>48157 Münster, Germany<br>phone:+49 251 93220,<br>email: info@weicon.de,<br>URL: www.weicon.de |
|---------------------------|--|

|  |                  |
|--|------------------|
| <b>e-mail address of person responsible for this SDS</b> | : msds@weicon.de |
|--|------------------|

|   |  |
|---|--|
| <b>Emergency telephone number (with hours of operation)</b> | : +1 202 464 2554<br>TRANSPORT (24 Hours/Day): +1 202 464 2554 |
|---|--|

### Section 2. Hazards identification

|                        |   |
|------------------------|---|
| <b>OSHA/HCS status</b> | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). |
|------------------------|---|

|   |  |
|---|--|
| <b>Classification of the substance or mixture</b> | : ACUTE TOXICITY (oral) - Category 4<br>SKIN CORROSION - Category 1B<br>SERIOUS EYE DAMAGE - Category 1<br>SKIN SENSITIZATION - Category 1 |
|---|--|

#### GHS label elements

##### Hazard pictograms



|                    |          |
|--------------------|----------|
| <b>Signal word</b> | : Danger |
|--------------------|----------|

|                          |  |
|--------------------------|--|
| <b>Hazard statements</b> | : H302 - Harmful if swallowed.<br>H314 - Causes severe skin burns and eye damage.<br>H317 - May cause an allergic skin reaction. |
|--------------------------|--|

#### Precautionary statements

|                   |  |
|-------------------|--|
| <b>Prevention</b> | : P280 - Wear protective gloves, protective clothing and eye or face protection. |
|-------------------|--|

|                 |  |
|-----------------|--|
| <b>Response</b> | : P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor.<br>P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting.<br>P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. |
|-----------------|--|

## Section 2. Hazards identification

- Storage** : Not applicable.
- Disposal** : P501 - Dispose of waste according to applicable legislation.
- Hazards not otherwise classified** : None known.
- Hazards identified when used** : No known significant effects or critical hazards.

## Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

| Ingredient name   | Synonyms | %         | Identifiers |
|---|----------|-----------|-------------|
| Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine |          | ≥10 - ≤25 | 186321-96-0 |
| benzyl alcohol  |          | ≥10 - ≤23 | 100-51-6    |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine  |          | ≤10       | 2855-13-2   |
| 3-aminopropyl dimethylamine   |          | ≤10       | 109-55-7    |
| Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines   |          | ≤10       | 68410-23-1  |
| 3-aminopropyltriethoxysilane  |          | ≤10       | 919-30-2    |
| 2,4,6-tris(dimethylaminomethyl)phenol   |          | ≤5        | 90-72-2     |
| m-phenylenebis(methylamine)   |          | ≤5        | 1477-55-0   |
| Phenol, styrenated  |          | ≤5        | 61788-44-1  |
| Amines, polyethylenepoly-, triethylenetetramine fraction  |          | ≤3        | 90640-67-8  |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

## Section 4. First aid measures

- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes severe burns. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst.

## Section 5. Fire-fighting measures

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## Section 7. Handling and storage

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name   | Exposure limits   |
|---|---|
| Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine<br>benzyl alcohol | None.<br><b>OARS WEEL (United States, 9/2024)</b><br>TWA 8 hours: 10 ppm.   |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine  | None.   |
| 3-aminopropyldimethylamine  | None.   |
| Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines   | None.   |
| 3-aminopropyltriethoxysilane  | None.   |
| m-phenylenebis(methylamine)   | <b>NIOSH REL (United States, 10/2020)</b><br>Absorbed through skin.<br>CEIL: 0.1 mg/m <sup>3</sup> .<br><b>CAL OSHA PEL (United States, 1/2025)</b><br>Absorbed through skin.<br>C: 0.1 mg/m <sup>3</sup> .<br><b>OSHA PEL 1989 (United States, 3/1989)</b><br>Absorbed through skin.<br>CEIL: 0.1 mg/m <sup>3</sup> .<br><b>ACGIH TLV (United States, 1/2025)</b><br>Absorbed through skin.<br>C: 0.018 ppm. |
| 2,4,6-tris(dimethylaminomethyl)phenol   | None.   |
| Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols  | None.   |
| Amines, polyethylenepoly-, triethylenetetramine fraction  | None.   |
| benzyl alcohol  | <b>OARS WEEL (United States, 9/2024)</b><br>TWA 8 hours: 10 ppm.  |

### Biological exposure indices

No exposure indices known.

**Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## Section 8. Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): Protective gloves made of nitrile rubber (material thickness of 0,4 mm); EN 374-5 Cat. III ; 4 - 8 hours (breakthrough time): Protective gloves made of Viton®/ butyl rubber (material thickness of 0,7 mm); EN388 Cat.II / EN374 Cat.III / EN374-2
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

- Physical state** : Liquid.
- Color** : Yellow. [Dark]
- Odor** : Characteristic.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point/freezing point** : Not available.
- Boiling point or initial boiling point and boiling range** : Not available.
- Flash point** : Closed cup: >94°C (>201.2°F)
- Evaporation rate** : Not available.
- Flammability** : Not available.
- Lower and upper explosion limit/flammability limit** : Not available.
- Vapor pressure** :

| Ingredient name                              | Vapor Pressure at 20°C |        |          | Vapor pressure at 50°C |     |        |
|--|------------------------|--------|----------|------------------------|-----|--------|
|  | mm Hg                  | kPa    | Method   | mm Hg                  | kPa | Method |
| 3-aminopropyl-dimethylamine                  | 4.42538                | 0.59   |          |                        |     |        |
| 2,4,6-tris(dimethylaminomethyl) phenol       | 0.06                   | 0.008  | EU A.4   |                        |     |        |
| benzyl alcohol                               | 0.05                   | 0.0067 |          |                        |     |        |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine | 0.01                   | 0.0013 | OECD 104 |                        |     |        |
| m-phenylenebis(methylamine)                  | 0.01                   | 0.0013 | OECD 104 |                        |     |        |

## Section 9. Physical and chemical properties

|   |        |         |          |  |  |  |
|---|--------|---------|----------|--|--|--|
| Amines, polyethylenepoly-, triethylenetetramine fraction                        | 0.0026 | 0.00035 | OECD 104 |  |  |  |
| Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines | 0      | 0       |          |  |  |  |

- Relative vapor density** : Not available.
- Relative density** : Not available.
- Density** : 1 g/cm<sup>3</sup> [23°C (73.4°F)]
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** :

| Ingredient name   | °C  | °F    | Method  |
|---|-----|-------|---------|
| 3-aminopropyldimethylamine  | 215 | 419   |         |
| 2,4,6-tris(dimethylaminomethyl)phenol   | 382 | 719.6 | EU A.15 |
| Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines | 398 | 748.4 |         |
| benzyl alcohol  | 436 | 816.8 |         |

- Decomposition temperature** : Not available.
- Viscosity** : Not available.
- Particle characteristics**
- Median particle size** : Not applicable.

## Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : No specific data.
- Incompatible materials** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

##### Product/ingredient name

benzyl alcohol

##### Result

##### Rat - Oral - LD50

1230 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Excitement Behavioral - Coma

##### Rabbit - Dermal - LD50

2000 mg/kg

##### Rat - Oral - LD50

1.57 g/kg

Toxic effects: Gastrointestinal - Hypermotility, diarrhea Kidney, Ureter, and Bladder - Changes in tubules (including acute renal failure, acute tubular necrosis)

3-aminopropyltriethoxysilane

## Section 11. Toxicological information

|                             |  |
|-----------------------------|--|
| m-phenylenebis(methylamine) | <p><b>Rabbit - Dermal - LD50</b><br/>4.29 g/kg<br/><u>Toxic effects:</u> Gastrointestinal - Ulceration or bleeding from stomach Kidney, Ureter, and Bladder - Other changes Skin After topical exposure - Primary irritation</p> <p><b>Rat - Oral - LD50</b><br/>930 mg/kg</p> <p><b>Rabbit - Dermal - LD50</b><br/>2 g/kg</p> <p><b>Rat - Inhalation - LC50 Gas.</b><br/>700 ppm [1 hours]<br/><u>Toxic effects:</u> Eye - Lacrimation Lung, Thorax, or Respiration - Respiratory depression</p>  |
| benzyl alcohol              | <p><b>Rat - Oral - LD50</b><br/>1230 mg/kg<br/><u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Behavioral - Excitement Behavioral - Coma</p> <p><b>Mouse - Oral - LD50</b><br/>1360 mg/kg</p> <p><b>Rabbit - Oral - LD50</b><br/>1040 mg/kg<br/><u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity)</p> <p><b>Mouse - Oral - LD50</b><br/>1360 mg/kg<br/><u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression</p> <p><b>Rat - Oral - LD50</b><br/>1660 mg/kg<br/><u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression</p> <p><b>Rabbit - Oral - LD50</b><br/>1040 mg/kg<br/><u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression</p> <p><b>Rabbit - Dermal - LD50</b><br/>2000 mg/kg</p> <p><b>Rat - Oral - LD50</b><br/>1.5 ml/kg</p> |

**Conclusion/Summary [Product]** : Not available.

### Skin corrosion/irritation

#### **Product/ingredient name**

benzyl alcohol

#### **Result**

##### **Man - Skin - Mild irritant**

Duration of treatment/exposure: 48 hours

Amount/concentration applied: 16 mg

##### **Pig - Skin - Moderate irritant**

Amount/concentration applied: 100 %

##### **Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

3-aminopropyltriethoxysilane

##### **Rabbit - Skin - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

m-phenylenebis(methylamine)

##### **Rabbit - Skin - Severe irritant**

## Section 11. Toxicological information

benzyl alcohol

Duration of treatment/exposure: 24 hoursAmount/concentration applied: 750 ug**Man - Skin - Mild irritant**Duration of treatment/exposure: 48 hoursAmount/concentration applied: 16 mg**Pig - Skin - Moderate irritant**Amount/concentration applied: 100 %**Rabbit - Skin - Moderate irritant**Duration of treatment/exposure: 24 hoursAmount/concentration applied: 100 mg

**Conclusion/Summary [Product]** : Not available.

### Serious eye damage/eye irritation

**Product/ingredient name**

m-phenylenebis(methylamine)

**Result**

**Rabbit - Eyes - Severe irritant**Duration of treatment/exposure: 24 hoursAmount/concentration applied: 50 ug

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

Not available.

### **Skin**

**Conclusion/Summary [Product]** : Not available.

### **Respiratory**

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

## Section 11. Toxicological information

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

### Information on the likely routes of exposure

Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes severe burns. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### **Long term exposure**

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

## Section 11. Toxicological information

### Numerical measures of toxicity

#### Acute toxicity estimates

| Product/ingredient name                      | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|--|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| WEICON Anti-Static Epoxy Hardener            | 2123.6       | 53728.8        | N/A                      | 194.7                      | 16.7                                |
| benzyl alcohol                               | 1620         | N/A            | N/A                      | N/A                        | 4.178                               |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine | 1030         | N/A            | N/A                      | N/A                        | N/A                                 |
| 3-aminopropyl dimethylamine                  | 500          | N/A            | N/A                      | N/A                        | N/A                                 |
| 3-aminopropyltriethoxysilane                 | N/A          | 4290           | N/A                      | 11                         | N/A                                 |
| m-phenylenebis(methylamine)                  | 930          | N/A            | N/A                      | N/A                        | 1.34                                |
| 2,4,6-tris(dimethylaminomethyl)phenol        | 500          | N/A            | N/A                      | N/A                        | N/A                                 |
| polyethylenepolyamines                       | 500          | 1100           | N/A                      | N/A                        | N/A                                 |
| benzyl alcohol                               | 1200         | N/A            | N/A                      | N/A                        | N/A                                 |

## Section 12. Ecological information

### Toxicity

#### Product/ingredient name

benzyl alcohol

#### Result

##### Acute - LC50 - Fresh water

Fish - Bluegill - *Lepomis macrochirus*  
10 ppm [96 hours]

Effect: Mortality

3-aminomethyl-3,5,5-trimethylcyclohexylamine

##### Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*

Age: <24 hours

17.4 mg/l [48 hours]

Effect: Intoxication

benzyl alcohol

##### Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas* - Juvenile (Fledgling, Hatchling, Weanling)

Age: 4 to 8 weeks; Size: 1.1 to 3.1 cm

460 mg/l [96 hours]

Effect: Mortality

##### Acute - LC50 - Fresh water

Fish - Bluegill - *Lepomis macrochirus*

10 ppm [96 hours]

Effect: Mortality

**Conclusion/Summary [Product]** : Not available.

### Persistence and degradability

Not available.

**Conclusion/Summary [Product]** : Not available.

### Bioaccumulative potential

## Section 12. Ecological information

| Product/ingredient name                                     | LogP <sub>ow</sub> | BCF  | Potential |
|---|--------------------|------|-----------|
| benzyl alcohol  | 0.87               | -    | Low       |
| 3-aminomethyl-  | 0.99               | -    | Low       |
| 3,5,5-trimethylcyclohexylamine                              |                    |      |           |
| 3-aminopropyldimethylamine                                  | -0.352             | -    | Low       |
| 3-aminopropyltriethoxysilane                                | 1.7                | 3.4  | Low       |
| 2,4,6-tris  | 0.219              | -    | Low       |
| (dimethylaminomethyl)phenol                                 |                    |      |           |
| m-phenylenebis(methylamine)                                 | 0.18               | 2.69 | Low       |
| Amines, polyethylenepoly-,<br>triethylenetetramine fraction | -2.65              | -    | Low       |

### Mobility in soil

**Soil/Water partition coefficient** : Not available.

### Other adverse effects

No known significant effects or critical hazards.








## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                                | DOT Classification | TDG Classification   | Mexico Classification  | IMDG  | IATA  |
|--------------------------------|--------------------|--|--|---|---|
| <b>UN number</b>               | Not available.     | UN3082   | UN3082   | UN1760  | UN1760  |
| <b>UN proper shipping name</b> | Not available.     | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine, Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine, Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines) | CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, 3-aminopropyldimethylamine) | CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, 3-aminopropyldimethylamine) |
|                                |                    |  |  |   |   |

## Section 14. Transport information

|                                   |                |  |   |  |  |
|-----------------------------------|----------------|--|---|--|--|
| <b>Transport hazard class(es)</b> | Not available. | 9<br>  | 9<br>  | 8<br>  | 8<br> |
| <b>Packing group</b>              | -              | III  | III   | II   | II   |
| <b>Environmental hazards</b>      | No.            | Yes.   | Yes.  | Yes.   | Yes. The environmentally hazardous substance mark is not required.                       |

### Additional information

#### **TDG Classification**

: Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark). Non-bulk packages of this product are not regulated as dangerous goods when transported by road or rail.

#### **Mexico Classification**

: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

#### **IMDG**

: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

#### **IATA**

: The environmentally hazardous substance mark may appear if required by other transportation regulations.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

## Section 15. Regulatory information

### U.S. Federal regulations

**TSCA 8(a) PAIR:** Phenol, styrenated

**TSCA 8(a) CDR Exempt/Partial exemption:** Not determined

### TSCA 12(b) - Chemical export notification

Not applicable.

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Not listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

## Section 15. Regulatory information

**Classification** : ACUTE TOXICITY (oral) - Category 4  
 SKIN CORROSION - Category 1B  
 SERIOUS EYE DAMAGE - Category 1  
 SKIN SENSITIZATION - Category 1

### Composition/information on ingredients

| Name  | %         | Classification  |
|---|-----------|---|
| Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine | ≥10 - ≤25 | SKIN IRRITATION - Category 2<br>SERIOUS EYE DAMAGE - Category 1<br>SKIN SENSITIZATION - Category 1  |
| benzyl alcohol  | ≥10 - ≤23 | ACUTE TOXICITY (oral) - Category 4<br>ACUTE TOXICITY (inhalation) - Category 4  |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine  | ≤10       | ACUTE TOXICITY (oral) - Category 4<br>ACUTE TOXICITY (dermal) - Category 4<br>SKIN CORROSION - Category 1B<br>SERIOUS EYE DAMAGE - Category 1<br>SKIN SENSITIZATION - Category 1      |
| 3-aminopropyl dimethylamine   | ≤10       | FLAMMABLE LIQUIDS - Category 3<br>ACUTE TOXICITY (oral) - Category 4<br>SKIN CORROSION - Category 1B<br>SERIOUS EYE DAMAGE - Category 1<br>SKIN SENSITIZATION - Category 1            |
| Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines   | ≤10       | SKIN IRRITATION - Category 2<br>SERIOUS EYE DAMAGE - Category 1<br>SKIN SENSITIZATION - Category 1  |
| 3-aminopropyltriethoxysilane  | ≤10       | ACUTE TOXICITY (inhalation) - Category 4<br>SKIN CORROSION - Category 1B<br>SERIOUS EYE DAMAGE - Category 1<br>SKIN SENSITIZATION - Category 1B                                       |
| 2,4,6-tris(dimethylaminomethyl)phenol   | ≤5        | ACUTE TOXICITY (oral) - Category 4<br>SKIN CORROSION - Category 1C<br>SERIOUS EYE DAMAGE - Category 1   |
| m-phenylenebis(methylamine)   | ≤5        | ACUTE TOXICITY (oral) - Category 4<br>ACUTE TOXICITY (inhalation) - Category 4<br>SKIN CORROSION - Category 1B<br>SERIOUS EYE DAMAGE - Category 1<br>SKIN SENSITIZATION - Category 1B |
| Phenol, styrenated  | ≤5        | SKIN IRRITATION - Category 2<br>SKIN SENSITIZATION - Category 1A  |
| Amines, polyethylenepoly-, triethylenetetramine fraction  | ≤3        | ACUTE TOXICITY (oral) - Category 4<br>ACUTE TOXICITY (dermal) - Category 4<br>SKIN CORROSION - Category 1B<br>SERIOUS EYE DAMAGE - Category 1<br>SKIN SENSITIZATION - Category 1      |

### State regulations

#### **Massachusetts**

: The following components are listed: BENZYL ALCOHOL; 3-(DIMETHYLAMINO)-PROPYLAMINE; M-XYLENE-ALPHA,ALPHA'-DIAMINE

#### **New York**

: None of the components are listed.

#### **New Jersey**

: The following components are listed: ISOPHORONEDIAMINE; 3-(DIMETHYLAMINO)PROPYLAMINE; m-XYLENE alpha, alpha'-DIAMINE

#### **Pennsylvania**

: The following components are listed: BENZENEMETHANOL; 1,3-PROPANEDIAMINE, N,N-DIMETHYL-; 1,3-BENZENED, IMETHANAMINE

#### **California Prop. 65**

This product does not require a Safe Harbor warning under California Prop. 65.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

## Section 15. Regulatory information

### Montreal Protocol

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

|                                |   |  |
|--------------------------------|---|--|
| <b>Australia</b>               | : | Not determined.  |
| <b>Canada</b>                  | : | Not determined.  |
| <b>China</b>                   | : | Not determined.  |
| <b>Eurasian Economic Union</b> | : | <b>Russian Federation inventory:</b> All components are listed or exempted.                      |
| <b>Japan</b>                   | : | <b>Japan inventory (CSCL):</b> Not determined.<br><b>Japan inventory (ISHL):</b> Not determined. |
| <b>New Zealand</b>             | : | All components are listed or exempted.   |
| <b>Philippines</b>             | : | Not determined.  |
| <b>Republic of Korea</b>       | : | Not determined.  |
| <b>Taiwan</b>                  | : | All components are listed or exempted.   |
| <b>Thailand</b>                | : | Not determined.  |
| <b>Turkey</b>                  | : | Not determined.  |
| <b>United States</b>           | : | Not determined.  |
| <b>Viet Nam</b>                | : | All components are listed or exempted.   |

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

|                  |   |   |
|------------------|---|---|
| Health           | / | 3 |
| Flammability     |   | 1 |
| Physical hazards |   | 0 |
|                  |   |   |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### National Fire Protection Association (U.S.A.)



### Procedure used to derive the classification

## Section 16. Other information

| Classification                     | Justification      |
|------------------------------------|--------------------|
| ACUTE TOXICITY (oral) - Category 4 | Calculation method |
| SKIN CORROSION - Category 1B       | Calculation method |
| SERIOUS EYE DAMAGE - Category 1    | Calculation method |
| SKIN SENSITIZATION - Category 1    | Calculation method |

### History

**Date of printing** : 2/3/2026  
**Date of issue/Date of revision** : 1/29/2026  
**Date of previous issue** : 11/4/2025  
**Version** : 2.6

### Key to abbreviations

: ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 DOT = Department of Transportation  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 IMO = International Maritime Organization  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 N/A = Not available  
 SGG = Segregation Group  
 TDG = Transportation of Dangerous Goods  
 UN = United Nations

### References

: Not available.

📌 Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.