

Anti-Spatter Spray HP



long-lasting effect | transparent | silicone-free

Anti-Spatter Spray HP is a high-quality release agent and lubricant and is used for cleaning welding tips, welding nozzles and gas nozzles. It also protects workpieces and surfaces to be welded from the adhesion and penetration of weld spatter without impairing the weld seam.

The silicone-free Anti-Spatter Spray provides long-term protection for the treated surfaces. Using the spray minimises downtimes and interruptions in the production process for cleaning the welding equipment.

The spray is excellent for use on stainless steel, but can also be applied to many other materials, such as aluminium, structural steel or non-ferrous metals.

The use of the spray eliminates the need to clean the workpieces with a spatula, brush or chisel. Post-treatment of the workpieces (such as bronzing, galvanising, anodising or painting) is possible without special cleaning.

Cleaning, e.g. with Cleaner Spray S, may be necessary in the case of excessive spraying.

Application

Apply to welding nozzles from approx. 15 cm. To protect the surface of the workpiece, apply the spray from approx. 25 cm and approx. 10 cm to the right and left of the weld seam.

In hollow bodies and confined spaces, do not start welding until the propellant has evaporated.

Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

10101563 Anti-Spatter Spray HP, 400 ml, transparent

Conversion table

(°C x 1.8) + 32 = °F

mm/25.4 = inch

µm/25.4 = mil

N x 0.225 = lb

N/mm² x 145 = psi

MPa x 145 = psi

Nm x 8.851 = lb·in

Nm x 0.738 = lb·ft

Nm x 141.62 = oz·in

mPa·s = cP

N/cm x 0.571 = lb/in

kV/mm x 25.4 = V/mil

Technical data

Base	Aerosol	
Odour	characteristic	
Colour	transparent	
Silicone-free	yes	
Minimum shelf life	at room temperature	36 mon.
Density	(+20 °C)	0,81 g/cm³
Flashpoint	>112 °C	
VOC (EG)	494,1 g/l VOC	

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Colombia S.A.S
Colombia
Phone: +57 314 793 86 06
Email: info@weicon.co

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.L.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr